

43073-LH,LUCITE ACRYLIC LACQUER GREEN

MSDS Number

BCDBQ

National Stock Number

8010-00K001527

Product Name

43073-LH,LUCITE ACRYLIC LACQUER GREEN

Manufacturer

E I DUPONT DE NEMOURS AND CO INC

Product Identification

Product ID:43073-LH,LUCITE ACRYLIC LACQUER GREEN

MSDS Date:01/01/1985

FSC:8010

NIIN:00K001527

MSDS Number: BCDBQ

Responsible Party

E.I. DUPONT DE NEMOURS & CO,INC.

1007 MARKET STREET

WILMINGTON , DE 19899

US

Emergency Phone: 800-441-7515

Info Phone: 800-441-7515

Cage: 19898

Contractor

E.I. DUPONT DE NEMOURS & CO., INC.

1635

WILMINGTON, DE 19898

US

800-441-7515;800-441-9442

Cage: 19898

Ingredients

ALIPHATIC ALCOHOL

Fraction By Weight: 8%

ACGIH TLV: 400 PPM

ALIPHATIC ESTER

Fraction By Weight: 7%

ACGIH TLV: 100 PPM

ALIPHATIC KETONE

Fraction By Weight: 12%

ACGIH TLV: 200 PPM

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 23%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 6%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:HEADACHE,NAUSEA,IMPAIRMENT OF REACTION TIME AND COORDINATION.

First Aid

First Aid:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER 15 MIN. KEEP WARM AND QUIET !

Fire Fighting

Flash Point:20-73F CC

Lower Limits:1.1

Upper Limits:12.8

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WEAR CHEM PROT. SUIT WITH SCBA. COOL CONTRS WITH H*20.

Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

Accidental Release

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK. EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions:DO NOT STORE ABOVE 120F.WASH THOROUGHLY BEFORE EATING OR SMOKING.OBSERVE LABEL PRECAUTIONS,CONTAINERS SHOULD BE GROUNDED WHEN POURING.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA RESPIR TC-23C IF CONTAMINANTS CONTROL NOT FEASIBLE.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:USE APPROPRIATE INDUSTRIAL HYGIENE PRACTICES.
Supplemental Safety and Health
NIOSH 6:1000379AS,ALIPHATIC PETRO. DISTILATE,3%,TLV-100PPM.NIOSH
7:CC4025000,ANTIMONY,CAS#7440-36-0,0.5,TLV-0.5MG/CUM.#8:1000768EE,E
THER ESTER,3% ,TLV-1100PPM(SEE ADDITIONAL DATA)

Chemical Properties

HCC:F3
Boiling Pt:B.P. Text:129-437F
Vapor Pres:37
Vapor Density:3.1
Spec Gravity:0.954
Evaporation Rate & Reference:Solubility in Water:APPRECIABLE
Appearance and Odor:LIQUID PAINT WITH CHARACTERISTIC ODOR.
Percent Volatiles by Volume:75.5

Stability

Stability Indicator/Materials to Avoid:YES
NONE REASONABLY FORESEEN.
Hazardous Decomposition Products:CO,CO*2,SMOKE,OXIDES OF METALS FOUND
IN HAZ INGREDIENTS SECT

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.