

NYLON XT-301EXPERIMENTAL/E13030-127E

MSDS Number

BCDCV

National Stock Number

9390-00K001552

Product Name

NYLON XT-301EXPERIMENTAL/E13030-127E

Manufacturer

E I DUPONT DE NEMOURS AND COMPANY INC

Product Identification

Product ID:NYLON XT-301EXPERIMENTAL/E13030-127E

MSDS Date:01/01/1985

FSC:9390

NIIN:00K001552

MSDS Number: BCDCV

Responsible Party

E.I.DUPONT DE NEMOURS & COMPANY,INC

Emergency Phone: (302) 774-2421

Cage: DO229

Contractor

E.I.DUPONT DE NEMOURS & CO INC

1635

BOSTON, MA 02118

US

800-441-7515

Cage: DO229

Ingredients

POLYOLEFIN MODIFIED POLYAMIDE

Fraction By Weight: 100%

Hazards

Effects of Overexposure:NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.

First Aid

First Aid:IF MOLTEN POLYMER CONTACTS SKIN,COOL RAPIDLY WITH COLD WATER & OBTAIN MEDICAL ATTENTION FOR THERMAL BURN.

Fire Fighting

Flash Point:APPROX 750F

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:USE PROTECTIVE EQUIPMENT SUCH AS GLOVES/SAFETY GLASSES.SWEEP UP TO PREVENT SLIPPINGK HAZARD ON POLYMER GRANULES.PLACE IN CLOSED CONTAINERS FOR LATER DISPOSAL.

Handling

Handling and Storage Precautions: DRY STORAGE. KEEP CONTAINER CLOSED TO PREVENT CONTAMINATION BY MOISTURE ABSORPTION.
Other Precautions: WEAR GLOVES WHEN NYLON IS HOT; USE SAFETY GLASSES DURING PROCESSING.

Exposure Controls

Respiratory Protection: NONE UNDER NORMAL PROCESSING
Ventilation: LOCAL EXHAUST AT MOLDING MACHINE
Protective Gloves: SEE OTHER PRECA
Eye Protection: SEE OTHER PRECAUTIONS
Other Protective Equipment: NONE
Supplemental Safety and Health
MFR SPECIFIED FLASH POINT 750F IS ESTIMATED BASED ON OTHER NYLONS USING ASTM D-1929 METHOD; ITEM FORMERLY KNOWN AS E13030-127E (SUPER TUF)

Chemical Properties

HCC: N1
Spec Gravity: 1.01
Evaporation Rate & Reference: UNKNOWN (NIL)
Solubility in Water: NEGLIGIBLE
Appearance and Odor: OFF-WHITE GRANULES; NO ODOR.

Stability

Stability Indicator/Materials to Avoid: YES
STRONG ACIDS & OXIDIZING AGENTS.
Stability Condition to Avoid: AVOID HEATING ABOVE 625F
Hazardous Decomposition Products: AMMONIA & CARBON MONOXIDE.

Disposal

Waste Disposal Methods: MFR SPECIFIES INCINERATION OR LANDFILL IN COMPLIANCE W/LOCAL STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.