

7941, SILVER COMPOSITION

MSDS Number

BCDDZ

National Stock Number

6850-00K001576

Product Name

7941, SILVER COMPOSITION

Manufacturer

E I DU PONT DE NEMOURS AND CO INC

Product Identification

Product ID:7941, SILVER COMPOSITION MSDS Date: 01/01/1985 FSC:6850 NIIN:00K001576 MSDS Number: BCDDZ

Responsible Party

E.I.DU PONT DE NEMOURS & CO,INC Emergency Phone: 302-774-2421

Cage: DO962

Contractor

E.I.DU PONT DE NEMOURS,INC.

WILMINGTON, DE 19898

US

800-441-7515;800-441-9442

Cage: DO962

Ingredients

SILVER, CAS# 7440-22-4

RTECS: VN3500000

Fraction By Weight: 70% ACGIH TLV: 0.01 MG/CUM

BUTYL CELLOSOLVE ACETATE, CAS# 112-07-2

CAS: 112-07-2 RTECS: KJ8925000

Fraction By Weight: 26%

EPOXY RESIN

Fraction By Weight: UNK

Hazards

Effects of Overexposure:FOR SOLVENT:VAPOR/LIQUID IRRITATS EYES, SKIN, NOSE, THROAT, TRANSIENT NAUS, HEADACHE. (SEE SUPP DATA)

First Aid

First Aid: INHALE: REMOVE TO FRESH AIR, GIVE CPR/O*2 IF



NEED; EYES/SKIN: FLUSH W LG AMTS H*20 FOR 15 MIN; INGEST: RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

Fire Fighting

Flash Point: 190F/88C COC

Lower Limits: 0.5 Upper Limits: 3.7

Extinguishing Media: CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures: WEAR SELF-CNTND BRTHG APP

Unusual Fire/Explosion Hazard:SOME MAT'L MAY BURN. CONT MAY EXPLODE IN

FIRE.

Accidental Release

Spill Release Procedures: DO NOT TOUCH SPILL MATL. SM SPILL: ABSORB W SAND, OTHER NON COMBUSTIBLES ABSORB; FLUSH W/H*20 LG SPILL: DIKE FAR AHEAD OF SPILL FOR LATER DISPOSAL. AVOID IGNITION SOURCES, PROLONGED BRTHNG

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED. MAINTAIN STRICT HYGIENE FOR CHEM HANDLING. Other Precautions:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR SMOKING.OBSERVE LABEL PRECAUTIONS.

Exposure Controls

Respiratory Protection: NO SPECIAL REQMNTS UNDER ORDINARY

CONDITIONS/ADEQUATE VENT.

Ventilation:LOCAL EXHAUST PREFERRED, MECHANICAL EXHAUST ACEPTABLE.

Protective Gloves: IMPERVIOUS

Eye Protection: CHEM SPLASH GOGGLES

Other Protective Equipment: USE APPROPIATE INDUSTRIAL HYGIENE PRACTICES.

Supplemental Safety and Health

OVEREXPOSURE: UNCURED EPOXY MAY CAUSE DENSENSITIVITY, OTHER ALLERGIC

REACTIONS.

Chemical Properties

HCC:V4

Boiling Pt:B.P. Text:378F/192C Vapor Pres:Vapor Density:5.5

Spec Gravity: 0.94

Evaporation Rate & Reference:>0.1(BU AC=1)

Solubility in Water: MODERATE

Appearance and Odor: NO INFO AVAILABLE.

Percent Volatiles by Volume: 100

Stability

Stability Indicator/Materials to Avoid:YES AVOID STRONG ALKALIES.

Hazardous Decomposition Products: CO*2, CO, TOXIC OXIDES SMOKE.

Disposal

Waste Disposal Methods: ELIMINATE IGNITION SOURCES. DESTROY BY LIQUID INCINERATION. INCINERATION WILL BE EASIER BY MIXING WITH A MORE FLAMMABLE SOLVENT. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, F ED, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.