

DUCO REFINISH THINNER, 3661-S

MSDS Number

BCDGX

National Stock Number

8010-00K001609

Product Name

DUCO REFINISH THINNER, 3661-S

Manufacturer

E I DUPONT DE NEMOURS AND COMPANY INC

Product Identification

Product ID:DUCO REFINISH THINNER, 3661-S

MSDS Date:01/01/1985

FSC:8010

NIIN:00K001609

MSDS Number: BCDGX

Responsible Party

E.I.DUPONT DE NEMOURS & COMPANY,INC

1007 MARKET STREET

WILMINGTON , DE 19899

US

Emergency Phone: 800-441-7515

Info Phone: 800-441-7515

Cage: DO229

Contractor

E.I.DUPONT DE NEMOURS & CO INC

1635

BOSTON, MA 02118

US

800-441-7515

Cage: DO229

Ingredients

ALIPHATIC PETRROLEUM DISTILLATE

Fraction By Weight: 27.0%

ACGIH TLV: 100 PPM(PER MFR)

ALIPHATIC ALCOHOL

Fraction By Weight: 19.0%

ACGIH TLV: 100PPM(PER MFR)

ALIPHATIC KETONE

Fraction By Weight: 27.0%

ACGIH TLV: 750PPM(PER MFR)

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 14.0%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ETHER ESTER;(SEE SUPPLEMENTAL DATA FOR OTHER HAZ

Fraction By Weight: 10.0%

ACGIH TLV: 50 PPM(PER MFR)

Hazards

Effects of Overexposure:CAUSES HEADACHE,NAUSEA,IMPAIRMENTK OF REACTION TIME AND COORDINATION.

First Aid

First Aid:INHALATION:MOVE TO FRESH AIR TO IMPROVE BREATHING;SKIN:WASH WITH SOAP & WATER.REMOVE CONTAMINATED CLOTHING;EYES:FLUSH WITH WATER FOR AT LEAST 15 MIN.CALL A PHYSICIAN.

Fire Fighting

Flash Point:Lower Limits:1.00

Upper Limits:18.0

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:COOL CLOSED CONTNRS W/H*20 USING FOG NOZZLES.

Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H*20 SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT,SHOVEL INTO METAL DRUMS:LG SPILL:DI KE W COMMERCIAL ABSORBENT,PUMP INTO COVERED DRUMS.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS & OPEN FLAMES.CLOSE CONTAINERS AFTER EACH USE.DO NOT STORE ABOVE 120F
Other Precautions:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR SMOKING;OBSERVE LABEL PRECAUTIONS;CONTAINERS SHOULD BE GROUNDED WHEN POURING.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA RESP TC-23C IF AIR CONTMNANTS CONTROL IS NOT FEASIBLE

Ventilation:LOCAL & MECH PROVIDE SUFFICIENT VENT TO KEEP BELOW TLV LEVEL

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:USE APPROPRIATE INDUSTRIAL HYGIENE PRACTICES.

Supplemental Safety and Health

MSDS FM MFR DATED:12/22/84;VAPOR PRESSURE 226.00& VAPOR DENSITY 2.00

NOTED BY MFR ARE OF PRINCIPAL SOLVENT;ALSO CONTAINS:4.3%

HYDROCARBON SOLVENT,TLV 25; SEE P/N IND"A" FOR OLD FORMULATION.

Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:129-350F
Vapor Pres:UNK
Vapor Density:UNK
Spec Gravity:0.797
Evaporation Rate & Reference:Solubility in Water:APPRECIABLE
Appearance and Odor:LIQUID THINNER W/CHARACTERISTIC ODOR
Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZERS, CORROSIVES
Stability Condition to Avoid:HEAT, IGNITION SOURCES
Hazardous Decomposition Products:CO,CO*2,SMOKE

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.