

TYZOR AA ORGANIC TITANATE

MSDS Number

BCDHQ

National Stock Number

6850-00K001623

Product Name

TYZOR AA ORGANIC TITANATE

Manufacturer

E I DUPONT DENEMOURS AND CO INC

Product Identification

Product ID:TYZOR AA ORGANIC TITANATE MSDS Date:01/01/1985 FSC:6850 NIIN:00K001623 MSDS Number: BCDHQ

Responsible Party

E.I.DUPONT DENEMOURS & CO,INC.

1007 MARKET STREET

WILMINGTON, DE 19899

US

Emergency Phone: 800-441-7515

Info Phone: 800-441-7515

Cage: GO769

Contractor

E.I.DUPONT DENEMOURS & COMPANY, INC

1635

WILMINGTON, DE 19899

US

800-441-7515

Cage: GO769

Ingredients

ISOPROPYL ALCOHOL, CAS#67-63-0

Fraction By Weight: 25% ACGIH TLV: 400 PPM

TITANIUM DI-ISOPROPOXY-DI-ACETYL-ACETONATE, CAS#17927-72-9.

Fraction By Weight: 75%

Hazards

Effects of Overexposure: EYES: CAUSE SEVERE BURNS. SKIN: MODERATE IRRITNT. SLIGHT ACUTE ORAL TOXICITY. SEE SUPPLEMENTAL DATA.

First Aid

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER



SYMPTOMS OF OVEREXPOSURE.

Fire Fighting

Flash Point:54F/12C PMCC

Lower Limits:UNK Upper Limits:UNK

Extinguishing Media:SM:H*20 ONLY;NO DRY CHEM. OR CO*2. LG:FLOOD

W.WATER.

Fire Fighting Procedures: SMALL AMOUNTS OF WATER MAY BE INEFFECTIVE. Unusual Fire/Explosion Hazard: FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS AND FLAMES.

Accidental Release

Spill Release Procedures: CONTAIN OR SOAK UP WITH SAND OR EARTH.

Handling

Handling and Storage Precautions: KEEP CONTAINER CLOSED.MOISTURE DEGRADES; KEEP DRY.STOREIN LOW FIRE RISK AREA.FREEZING AFFECTS PHYSICAL CONDITION BUT WILL NOT DAMAGE.

Other Precautions: PREVENT BODILY CONTACT. WASH THOROUGHLY AFTER HANDLING. NOT CORROSIVE TO STEEL, BUT PROMOTES RUSTING OF IRON METALS.

Exposure Controls

Respiratory Protection: NO SPECIAL REQMNTS UNDER ORDINARY

CONDITIONS/ADEQUATE VENT.

Ventilation: NO SPECIAL REQUIREMENTS W ADEQUATE VENT.

Protective Gloves: IMPERVIOUS

Eye Protection: CHEM SPLASH GOGGLES

Other Protective Equipment: AS REQUIRED TO PREVENT PROLONGED CONTACT.

Supplemental Safety and Health

SYNONYMS:TITANIUM DI-ISOPROPYL-DI-ACETYLACETONE;TITANIUM

ACETYLACETONATE.OVEREXPOSURE:REPEATED CONTACT/INHALE OF PROPANOL

CAUSES CNS DEPRESS & NARCOSIS.

Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:185F/85C

Vapor Pres:67 Vapor Density:UNK Spec Gravity:0.99

Evaporation Rate & Reference: NOT AVAILABLE

Solubility in Water: DISPERSABLE

Appearance and Odor: CLEAR LIQUID, RED; SOUR RANCID UNPLEASANT ODOR.

Percent Volatiles by Volume:25

Stability

Stability Indicator/Materials to Avoid:YES SLOWLY HYDROLYZED BY WATER.

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: FLAMMABLE ISOPROPYL ALCOHOL IS FORMED BY HYDROLYSIS.

Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.