

# **AUTOMATIC BLANKET WASH 4-1235**

### **MSDS Number**

**BCDSP** 

#### **National Stock Number**

6850-00N000115

## **Product Name**

**AUTOMATIC BLANKET WASH 4-1235** 

### Manufacturer

A B DICK COMPANY

# **Product Identification**

Product ID:AUTOMATIC BLANKET WASH 4-1235 MSDS Date:01/01/1987 FSC:6850 NIIN:00N000115 MSDS Number: BCDSP

# **Responsible Party**

A.B.DICK COMPANY

5700 WEST TOUHY AVENUE

CHICAGO, IL 60648-4606

US

Emergency Phone: 312-647-8800

Info Phone: 312-547-8800

Cage: HO951

Contractor

DICK A B CO

CHICAGO, IL 60648

US

312-647-8800 Cage: HO951

## **Ingredients**

PETROLEUM DISTILLATES (ALIPHATIC) (C\*9,12%; C\*10,56%;

ACGIH TLV: 300 PPM (MFR)

PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III)

CAS: 127-18-4 RTECS: KX3850000 Fraction By Weight: 45%

raction by Weight. 45 /

OSHA PEL100 PPM

ACGIH TLV: 25PPM/100,A3 STEL;94

EPA Report Quantity: 100 LBS DOT Report Quantity: 100 LBS

# Hazards

Effects of Overexposure:INH:HDCH,DIZ,VERTIGO. SKIN:PRLNG/RPTD



CONTCT-MOD IRRIT, DEFAT, DERMAT. EYE: SEV IRRIT (SEE SUPP DATA)

#### First Aid

First Aid:INH: MOVE TO FRESH AIR, CONTACT MD IF SEV EXPOS OCCURRED. INGEST: DO NOT INDUCE VOMITING. CALL MD IMMED. SKIN: WASH AREA W/SOAP & WATER. EYES: FLUSH W/WATER AT LEAST 15 MIN & CONTACT MD IMMED.

# Fire Fighting

Flash Point:119 TCC Lower Limits:UNK Upper Limits:UNK

Extinguishing Media: FOAM, CO\*2, DRY CHEMICAL

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPAR, FULL

PROTECTIVE CLOTHES

Unusual Fire/Explosion Hazard: POSSIBLE TOXIC COMBUSTION PRODUCTS:

CHLORIDES, PHOSGENE

### **Accidental Release**

Spill Release Procedures: WIPE UP W/DRY CLOTH. MATERIAL IS COMBUSTIBLE & CARE SHOULD BE TAKEN TO AVOID FIRE. REMOVE ANY POSSIBLE IGNITION SOURCE.

#### Handling

Handling and Storage Precautions: DO NOT STORE NEAR FIRE OR FLAME. NO SMOKING IN AREA OF USE. HEAT &/OR UV RADIATION MAY CAUSE FORMATION OF HCL &/OR PHOSGENE.

Other Precautions: APPROX 20 CU FT OF AIR SHOULD BE BROUGHT INTO THE DUPLICATING AREA FOR EVERY MASTER CLEAN-UP. INCR TO 35 CU FT IF USED IN COMBINATION W/AN ELECTROFAX OFFSET MASTET SYSTEM.

## **Exposure Controls**

Ventilation: SEE OTHER PRECAUTIONS

Protective Gloves: RUBBER

Eye Protection: NOT NORMALLY NECESSARY

Supplemental Safety and Health

DATE OF PREP: OCT 31,1985. OVEREXPOS: EYES CONT: REDNESS, TEARING.

INGEST: LD50 (RAT)=5840 MG/KG. IRRIT OF G.I. TRACT, INCLUDING

NAUSEA, VOMITING & DIARRHEA.

## **Chemical Properties**

Boiling Pt:B.P. Text:250-350F

Vapor Pres:10 Vapor Density:>1.0 Spec Gravity:0.998

Solubility in Water: INSOLUBLE

Appearance and Odor: GREEN LIQUID, GASOLINE ODOR

Percent Volatiles by Volume:100

## Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid: EXPOSURE TO OPEN FLAMES.

Hazardous Decomposition Products: TOXIC FUMES OF CHLORIDES & PHOSGENE Conditions to Avoid Polymerization: EXPOSURE TO OPEN FLAMES.

### **Disposal**

Waste Disposal Methods: USE APPROVED DISPOSAL METHOD FOR COMBUSTIBLE FLUIDS CONTAINING CHLORINATED MATERIAL. FOLLOW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their





particular situation.