

SOVAPON TANK COATING 264-W-12B

MSDS Number

BCFYW

National Stock Number

8030-00N000655

Product Name

SOVAPON TANK COATING 264-W-12B

Manufacturer

MOBIL CHEMICAL COMPANY

Product Identification

Product ID:SOVAPON TANK COATING 264-W-12B

MSDS Date:01/01/1985

FSC:8030

NIIN:00N000655

MSDS Number: BCFYW

Responsible Party

MOBIL CHEMICAL COMPANY

Emergency Phone: (212) 883-5368

Cage: 29430

Contractor

MOBIL CHEMICAL CO DIV OF MOBIL OIL CORP

250

EDISON, NJ 08818

US

Cage: 29430

Ingredients

AROMATIC HYDROCARBON

Fraction By Weight: 20.0%

ACGIH TLV: 100 PPM-MFG

2-ETHOXYETHANOL (EGEE) (SARA III)

CAS: 110-80-5

RTECS: KK8050000

Fraction By Weight: 5.0%

OSHA PELs,200 PPM

ACGIH TLV: S, 5 PPM; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:EYE & RESPIRATORY TRACT IRRITANT. DIZZINESS, NAUSEA, UNCONSCIOUSNESS. REDNESS OR DRYNESS OF SKIN.

First Aid

First Aid:VAPOR: REMOVE VICTOM TO FRESH AIR. RESUSCITATE IF NEEDED. GET MEDICAL ATTENTION. EYE: FLUSH WITH WATER 15 MINUTES CONSULT PHYSICIAN. SKIN: WASH WITH SOAP & WATER.

Fire Fighting

Flash Point:116F PMCC

Lower Limits:1.0

Upper Limits:14.0

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM OR WATER FOG.

Fire Fighting Procedures:SELF-CONTAINED OBA OR AIR MASK

Unusual Fire/Explosion Hazard:KEEP CONTAINERS EXPOSED TO FIRE COOL WITH WATER SPRAY

Accidental Release

Spill Release Procedures:VENTILATE AREA. AVOID BREATHING VAPOR. USE SELF-CONTAINED OBA OR AIR MASK FOR LARGE SPILLS IN CONFINED AREA. AVOID EYE CONTACT. WIPE-UP OR ABSORB ON SUITABLE MATERIAL & SHOVEL-UP.

Handling

Handling and Storage Precautions:DO NOT FLAME CUT, BRAZE OR WELD WITHOUT APPROVED RESPIRATOR OR ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. AVOID EYE CONTACT.

Other Precautions:AVOID PROLONGED OR REPEATED CONTACT WITH SKIN & BREATHING OF VAPORS OR SPRAY MIST. KEEP CONTAINER CLOSED.

Exposure Controls

Respiratory Protection:USE APPROVED DEVICE FOR CONFINED AREA & SPRAY APPLICATIONS.

Ventilation:REQUIRED IN CONFINED AREA. EQUIPMENT MUST BE EXPLOSION-PROOF

Protective Gloves:RECOMMENDED

Eye Protection:GOGGLES FOR PAINTING

Other Protective Equipment:USUAL CLOTHING FOR PAINTING OPERATIONS

Supplemental Safety and Health

CONFORMS TO MIL-P-23236, TY 1,CLASS 1. PART A OF A TWO PART PRODUCT. FOR PART B INFO SEE:SOVAPON CURING AGENT 264-T-24.

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:273F

Vapor Pres:4.0

Vapor Density:4.7

Spec Gravity:1.59

Evaporation Rate & Reference:0.3 BUTACE

Appearance and Odor:NORMAL FOR PAINT OR COATING TYPE PRODUCT

Percent Volatiles by Volume:46.0

Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO*2, CO

Disposal

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE OF

IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.