

VF-182

MSDS Number

BCGBH

National Stock Number

6810-00N000686

Product Name

VF-182

Manufacturer

NAZ DAR COMPANY

Product Identification

Product ID:VF-182
MSDS Date:01/01/1985
FSC:6810
NIIN:00N000686
MSDS Number: BCGBH

Responsible Party

NAZ DAR COMPANY
Emergency Phone: (312) 943-8338
Cage: DO971

Contractor

NAZDAR COMPANY
CHICAGO, IL 60622-4292
US
312-943-8338;800-736-7636
Cage: 76708

Ingredients

ISOPHORONE (SARA III)
CAS: 78-59-1
RTECS: GW7700000
OSHA PEL25 PPM
ACGIH TLV: C 5 PPM; 9293
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

50%)

Hazards

Effects of Overexposure:INH: ANESTH. IRRIT RESP TRACT OR ACUTE CNS
DEPRSS W/HDCH,DIZ,STAG,UNCON,COMA. SKIN/EYE: IRRITATION.

First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE. RESTORE BRTHNG. KEEP WARM &
QUIET. NOTIFY MD. SPLASH: (EYES) FLUSH IMMED W/LG AMT OF WATER AT
LEAST 15 MIN. TAKE TO MD FOR DEFINITIVE TREATMENT. SPLASH (SKIN)
REMOVE W/SOA P & WATER. REMOVE CONTAMINATED CLOTHING.

Fire Fighting

Flash Point:122F TCC
Lower Limits:0.8
Extinguishing Media:CO*2, DRY CHEMICAL OR FOAM FOR CLASS 1B FLAM LIQ FIRES
Fire Fighting Procedures:USE WATER TO COOL CLSD CANS, FOG NOZZLES ARE PREFERABLE
Unusual Fire/Explosion Hazard:KEEP CANS TIGHTLY CLSD. KEEP FROM IGNIT SOURCES. CLSD CAN MAY EXPLO FROM EXTRM HEAT. AVOID HOT SURFC

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID BRTHNG VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LG QTY IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS. DO NOT TAKE INTERNALLY
Other Precautions:GROUND CONTAINERS WHEN POURING. AVOID FREE FALL OF LIQ IN EXCESS OF A FEW INCHES. DO NOT FLAME CUT, BRAZE, OR WELD W/O NIOSH/MSHA APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPRVD RESP PROT FOR PARTICULAR EXPOS OF CONCERN.
Ventilation:GEN DILTN/LOCAL EXHST KEEP BELOW TLV/LEL,REMV DECOMP PRODCTS
Protective Gloves:YES
Eye Protection:YES
Other Protective Equipment:PREVENT PRLNGD SKIN CNTCT W/CONTAMINATED CLOTHING.
Supplemental Safety and Health
VAPOR PRESSURE: 5.5 AT 100F. FLASH PT GIVEN IS FOR TS-2S SOLVENT.

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:333-420F
Vapor Density:>1.0
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:POSS FUMES IF HEATED TO DECOMP: CO & OXIDES OF NITROGEN.

Disposal

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE IAW FED., STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.