

820218,TEFLON DRY LUBRICANT AEROSOL 6615N

MSDS Number

BCGTZ

National Stock Number

9150-00N000996

Product Name

820218,TEFLON DRY LUBRICANT AEROSOL 6615N

Manufacturer

E I DUPONT DE NEMOURS AND CO

Product Identification

Product ID:820218,TEFLON DRY LUBRICANT AEROSOL 6615N

MSDS Date:01/01/1985

FSC:9150

NIIN:00N000996

MSDS Number: BCGTZ

Responsible Party

E.I.DUPONT DE NEMOURS AND CO.

1007 MARKET STREET

WILMINGTON , DE 19899

US

Emergency Phone: 800-441-7515

Info Phone: 800-441-7515

Cage: DO229

Contractor

E.I.DUPONT DE NEMOURS & CO INC

1635

BOSTON, MA 02118

US

800-441-7515

Cage: DO229

Ingredients

ALIPHATIC HYDROCARBONS

Fraction By Weight: 26%

ACGIH TLV: 500 PPM

ISOBUTANE,CAS# 75-28-5,(AS PROPELLANT)

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: >53%

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight:

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

Hazards

Effects of Overexposure: HEADACHE, NAUSEA, IMPAIRMENT OF REACTION TIME AND COORDINATION

First Aid

First Aid: INHALATION-MOVE TO FRESH AIR TO RESTORE BREATHING. SKIN CONTACT-WASH WITH SOAP AND WATER, REMOVE CONTAMINATED CLOTHING. EYE CONTACT-FLUSH WITH WATER FOR AT LEAST 15 MINUTES, CALL A PHYSICIAN.

Fire Fighting

Flash Point: FLAMMABLE GAS

Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures: WATER FROM FOG NOZZLE TO COOL CLOSED CONTAINERS

Unusual Fire/Explosion Hazard: CONTENTS UNDER PRESSURE, MAY CARRY A FLAME FRONT, IN ENCLOSURE AN EXPLOSION

Accidental Release

Spill Release Procedures: AVOID PROLONGED CONTACT WITH SKIN AND BREATHING OF VAPOR. REMOVE SOURCES OF IGNITION. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. VENTILATE AREA.

Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. DO NOT STORE ABOVE 120°F. DO NOT PUNCTURE CAN OR INCINERATE. CLOSE CONTAINER AFTER EACH USE.

Other Precautions: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR SMOKING. OBSERVE LABEL PRECAUTIONS. CONTAINERS SHOULD BE GROUNDED WHEN POURING.

Exposure Controls

Respiratory Protection: NIOSH/MSHA APPRVD RESP PROTECT REQ FOR INADEQUATE VENTILATION

Ventilation: LOCAL EXHAUST TO MAINTN BELOW TLV AND LEL.

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY EYEWEAR

Other Protective Equipment: USE APPROPRIATE INDUSTRIAL HYGIENE PRACTICES.

Supplemental Safety and Health

THIS PRODUCT REPLACES SLIPSPRAY DRY LUBRICANT AEROSOL AS OF 18 FEB 82.

Chemical Properties

HCC: V3

Boiling Pt: B.P. Text: 190-287°F

Vapor Pres: 10

Vapor Density: 2.5

Spec Gravity: 0.838

Evaporation Rate & Reference: >1 (ETHER=1)

Solubility in Water: NEGLIGIBLE

Appearance and Odor: AEROSOL MIST WHEN SPRAYED; MILD SOLVENT ODOR.

Percent Volatiles by Volume: AT30

Stability

Stability Indicator/Materials to Avoid: YES

NONE REASONABLY FORESEEABLE

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, SMOKE.

Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE

INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.