

## **Y-4695, SPRD LUSTRE DP TNT 5**

### **MSDS Number**

BCGXM

### **National Stock Number**

8010-00N001052

### **Product Name**

Y-4695, SPRD LUSTRE DP TNT 5

### **Manufacturer**

GLIDDEN COATING AND RESINS

### **Product Identification**

Product ID:Y-4695, SPRD LUSTRE DP TNT 5

MSDS Date:01/01/1985

FSC:8010

NIIN:00N001052

MSDS Number: BCGXM

### **Responsible Party**

GLIDDEN COATING & RESINS

925 EUCLID AVE

CLEVELAND , OH 44115

US

Cage: GO971

### **Contractor**

GLIDDEN COATING & RESINS

CLEVELAND, OH 44115

US

216-344-8000

Cage: GO971

### **Ingredients**

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 19%

OSHA PEL100 PPM

ALIPHATIC HYDROCARBON (SHELL SOL-140)

Fraction By Weight: 7%

ISOPARAFINIC HYDROCARBONS (ISOPAR K,SHELL SOL >1)

Fraction By Weight: 10%

### **Hazards**

Effects of Overexposure:IRRITATION OF EYES,SKIN,AND RESP  
TRACT.DERMATITIS ON REPEAT & PROLONG SKIN CONTACT

### **First Aid**

First Aid: INHAL: REMOVE TO FRESH AIR, RESTORE BREATH, GET MED ATTN. SKIN  
CONT: WIPE WITH CLEAN CLOTH, WASH WITH SOAP AND WATER. EYE CONT; FLUSH  
THOROUGHLY WITH WATER, GET MED ATTN.

## Fire Fighting

Flash Point: 102F TCC  
Lower Limits: 1.1  
Extinguishing Media: CO\*2, DRY CHEMICAL, FOAM  
Fire Fighting Procedures: WATER SPRAY TO COOL CONTAINERS  
Unusual Fire/Explosion Hazard: CLOSED CONT MAY EXPLODE WHEN EXPOSED TO  
EXTREME HEAT OR FIRE.

## Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE  
AREA. MOP SPILL WITH INERT ABSORBENT. BURN SWEEPINGS IN A SAFE AREA.

## Handling

Handling and Storage Precautions: STORE BELOW 100F. KEEP CONTAINERS  
CLOSED AND AWAY FROM HEAT AND OPEN FLAME.  
Other Precautions: AVOID PROLONGED CONTACT WITH SKIN, AND BREATHING  
VAPORS OR SPRAY MIST. DO NOT TAKE INTERNALLY.

## Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH  
EXPOSURE OF CONCERN  
Ventilation: DILUTION OF LOCAL EXHAUST TO MAINTAIN BELOW TLV.  
Protective Gloves: SOLVENT RESIST  
Eye Protection: SPLASH PROOF GOGGLES  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt: B.P. Text: 313-410F  
Vapor Density: > 1  
Evaporation Rate & Reference: SLOWER THAN ETHER  
Percent Volatiles by Volume: 53.8

## Stability

Stability Indicator/Materials to Avoid: YES  
AVOID CONTAMINATION WITH FOREIGN MATERIALS  
Hazardous Decomposition Products: NO

## Disposal

Waste Disposal Methods: DISPOSE IAW LOCAL REGULATIONS. DO NOT INCINERATE  
CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.