

## **V LUBE**

### **MSDS Number**

BCLKG

### **National Stock Number**

9150-00N004007

### **Product Name**

V LUBE

### **Manufacturer**

PENNWALT CORP STOKES DIV

### **Product Identification**

Product ID: V LUBE  
MSDS Date: 01/01/1985  
FSC: 9150  
NIIN: 00N004007  
MSDS Number: BCLKG

### **Responsible Party**

PENNWALT CORPORATION, STOKES DIVISION  
Emergency Phone: 215-289-0100  
Cage: 7K913

### **Contractor**

PENNWALT CORPORATION/ELF ATOCHEM NORTH AMERICA  
PHILADELPHIA, PA 19102  
US  
215-587-7711  
Cage: 7K913

### **Ingredients**

SOLVENT REFINED PARAFFINIC OIL  
Fraction By Weight: 79.6%

ETHYLENE/PROPYLENE COPOLYMER  
Fraction By Weight: 13.3%

MAGNESIUM  
CAS: 7439-95-4  
RTECS: OM2100000

NITROGEN  
CAS: 7727-37-9  
RTECS: QW9700000  
ACGIH TLV: ASPHYXIAN; 9192

PHOSPHORUS

CAS: 7723-14-0

RTECS: TH3495000

ACGIH TLV: 0.1MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

## Hazards

Effects of Overexposure:EYES: MILD TRANSIENT IRRIT. SKIN: PRLNG CONT SLIGHT IRRIT.

## First Aid

First Aid:EYES: FLUSH W/ PLENTY OF WATER FOR 15 MIN. SKIN: FLUSH WITH SOAP AND WATER. INHAL: REMOVE TO FRESH AIR. INGEST: INDUCE VOMIT, GET MEDICAL ATTENTION.

## Fire Fighting

Flash Point:370F; 188C (COC)

Extinguishing Media:WATER FOG, CO\*2, DRY CHEMICAL, FOAM, SAND.

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

## Accidental Release

Spill Release Procedures:ABSORB WITH SAND OR INERT MATERIAL. SWEEP OR SCOOP UP AND REMOVE.

## Handling

Handling and Storage Precautions:STORE AS CLASS III B LIQUID PER NFPA.

## Exposure Controls

Respiratory Protection:MFR STATES NOT REQUIRED

Ventilation:USE LOCAL EXHAUST TO KEEP BELOW TLV

Protective Gloves:SEE PROT EQUIP

Eye Protection:SAFETY GLASSES

Other Protective Equipment:GLOVES POLYVINYL CHLORIDE/NEOPRENE FOR PRLNG CONTACT.

Supplemental Safety and Health

INGREDIENTS: SULFUR, ZINC, VP: NIL. % VOLATILE BY VOL: NIL

## Chemical Properties

Boiling Pt:B.P. Text:WIDE RANGE

Vapor Density:>10

Spec Gravity:0.88

Evaporation Rate & Reference:0.001 (ETHER=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:DARK AMBER FLUID, LUBE OIL ODOR

## Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:OPEN FLAMES

Hazardous Decomposition Products:CO, TRACE OXIDES OF SULFUR, ASPHYXIANTS

## Disposal

Waste Disposal Methods:MFR RECOMMENDS INCINERATION OR BURYING IN A SANITARY LANDFILL. DISPOSAL METHOD MUST BE IAW FEDERAL, STATE ANS LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.