

AQUAPON FLOOR PATCH,97-180,COMP A

MSDS Number

BCLWX

National Stock Number

8010-00N006075

Product Name

AQUAPON FLOOR PATCH, 97-180, COMP A

Manufacturer

PPG INDUSTRIES INC

Product Identification

Product ID:AQUAPON FLOOR PATCH,97-180,COMP A MSDS Date:01/01/1985 FSC:8010 NIIN:00N006075 MSDS Number: BCLWX

Responsible Party

PPG INDUSTRIES, INC

Emergency Phone: 412-434-3131

Cage: GO796

Contractor

PPG INDUSTRIES, INC. COATINGS TRESINS DIV.

PITTSBURGH, PA 15272

304-843-1300

US

Cage: G0796

Ingredients

EPOXY RESIN

Fraction By Weight: 95%

ACGIH TLV: 50 PPM

LEAD (SARA III) CAS: 7439-92-1 RTECS: OF7525000

Fraction By Weight:

OSHA PEL0.05 MG/M3;1910.1025

ACGIH TLV: 0.15 MG/M3; DUST 9192

EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

Hazards

Effects of Overexposure: EYE/SKIN: IRRIT. VAPORS: ANESTHETIC, IRRIT OF RESP TRACT, ACUTE NERVOUS SYSTEM DEPRESSION, COMA

First Aid

First Aid: EYE: FLUSH WITH WATER 15 MINUTES, GET MEDICAL ATTN. SKIN: WASH



WITH WATER, REMOVE CONTAMINATED CLOTHING, CONSULT PHYSICIAN. INHALATION: REMOVE FROM EXPOSURE, RESTORE BREATHING, CONSULT PHYSICIAN.

Fire Fighting

Flash Point:167F/75C (PMCC)

Lower Limits: 1.2

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: SELF-CONT BREATH APP, WATER FOG TO COOL EXPOSED

CONTAINERS

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN

EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: SECURE SOURCES OF IGNITION, AVOID BREATHING VAPORS, VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F/48C. DO NOT TAKE INTERNALLY. GROUND CONTAINER WHEN POURING, AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

Other Precautions: DO NOT FLAME CUT, BRAZE OR WELD WITHOUT NIOSH/MSHA APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH

EXPOSURE OF CONCERN.

Ventilation:LOCAL/MECHANICAL TO KEEP EXPOSURE BELOW TLV.

Protective Gloves: REQUIRED Eye Protection: SPLASH GOGGLES

Other Protective Equipment: AS REQUIRED TO PREVENT SKIN CONTACT

Supplemental Safety and Health

PART A OF A TWO PART KIT. PART B ID CODE: 97-181.

Chemical Properties

Boiling Pt:B.P. Text:243F/117C

Vapor Density:>1

Evaporation Rate & Reference:Percent Volatiles by Volume:0.1

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CARBON MONOXIDE

Disposal

Waste Disposal Methods: COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.