

# **AQUAPON FLOOR PATCH,97-181,COMP B**

## **MSDS Number**

**BCLWY** 

#### **National Stock Number**

8010-00N006075

## **Product Name**

AQUAPON FLOOR PATCH,97-181,COMP B

#### Manufacturer

PPG INDUSTRIES INC

## **Product Identification**

Product ID:AQUAPON FLOOR PATCH,97-181,COMP B MSDS Date:01/01/1985

FSC:8010 NIIN:00N006075 MSDS Number: BCLWY

# **Responsible Party**

PPG INDUSTRIES, INC

Emergency Phone: 412-434-3131

Cage: GO796

### **Contractor**

PPG INDUSTRIES, INC. COATINGS TRESINS DIV.

PITTSBURGH, PA 15272

304-843-1300

US

Cage: GO796

## **Ingredients**

DIETHYLENE TRIAMINE

CAS: 111-40-0

RTECS: IE1225000

Fraction By Weight:

OSHA PEL1 PPM

ACGIH TLV: S, 1 PPM; 9192

LEAD (SARA III)

CAS: 7439-92-1

RTECS: OF7525000

Fraction By Weight:

OSHA PEL0.05 MG/M3;1910.1025 ACGIH TLV: 0.15 MG/M3;DUST 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

## **Hazards**

Effects of Overexposure: EYE/SKIN: IRRIT. VAPORS: ANESTHETIC, IRRIT OF



#### RESP TRACT, ACUTE NERVOUS SYSTEM DEPRESSION, COMA

#### First Aid

First Aid:EYE: FLUSH WITH WATER 15 MINUTES,GET MEDICAL TREATMENT. SKIN: WASH WITH WATER,REMOVE CONTAMINATED CLOTHING,CONSULT PHYSICIAN.

INHALATION: REMOVE FROM EXPOSURE, RESTORE BREATHING, NOTIFY

PHYSICIAN.

## Fire Fighting

Flash Point:>200F/93C (PMCC)

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: SELF-CONT BREATH APP, WATER FOG TO COOL EXPOSED

CONTAINERS

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN

WXPOSED TO EXTREME HEAT.

### **Accidental Release**

Spill Release Procedures: SECURE SOURCES OF IGNITION. AVOID BREATHING VAPORS, VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

## Handling

Handling and Storage Precautions: STORE BELOW 120F/48C. GROUND CONTAINER WHEN POURING, AVOID FREE FALL IN EXCESS OF A FEW INCHES. DO NOT TAKE INTERNALLY

Other Precautions: DO NOT FLAME CUT, BRAZE OR WELD WITH OUT NIOSH/MSHA RESPIRATOR PROTECTION OR ADEQUATE VENTILATION.

### **Exposure Controls**

Respiratory Protection: NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH

EXPOSURE OF CONCERN

Ventilation:LOCAL/MECHANICAL TO MAINTAIN BELOW TLV

Protective Gloves: REQUIRED Eye Protection: SPLASH GOGGLES.

Other Protective Equipment: AS REQUIRED TO PREVENT SKIN CONTACT

Supplemental Safety and Health

PART B OF A TWO PART KIT. PART A ID CODE: 97-180

## **Chemical Properties**

Vapor Pres:0.2 Vapor Density:>1

Evaporation Rate & Reference:

#### Stability

Stability Indicator/Materials to Avoid:YES

ACIDS

Hazardous Decomposition Products: CARBON MONOXIDE

## Disposal

Waste Disposal Methods: COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.