

F65 E 1,KEM LUSTRAL ENAMEL,ORANGE

MSDS Number

BCMBT

National Stock Number

8010-00N006147

Product Name

F65 E 1,KEM LUSTRAL ENAMEL,ORANGE

Manufacturer

THE SHERWIN WILLIAMS COMPANY

Product Identification

Product ID:F65 E 1,KEM LUSTRAL ENAMEL,ORANGE

MSDS Date:01/01/1985

FSC:8010

NIIN:00N006147

MSDS Number: BCMBT

Responsible Party

THE SHERWIN-WILLIAMS COMPANY

101 PROSPECT AVE N W

CLEVELAND , OH 44115-1042

US

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: DO693

Contractor

THE SHERWIN-WILLIAMS CO

CLEVELAND, OH 44115

US

216-566-2902

Cage: DO693

Ingredients

LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

CAS: 7758-97-6

RTECS: GB2975000

Fraction By Weight: 8.5%

OSHA PEL0.05 MG/M3 (PB)

ACGIH TLV: 0.05MG/M3(CR)A2;8990

LEAD (SARA III)

CAS: 7439-92-1

RTECS: OF7525000

OSHA PEL0.05 MG/M3;1910.1025

ACGIH TLV: 0.15 MG/M3;DUST 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 40%

OSHA PEL100 PPM

Hazards

Effects of Overexposure:VAPOR: ANESTHETIC,RESP TRACT
IRRIT,LIGHTHEADEDNESS.EYE:IRRIT. SKIN: IRRIT,ULCERS,NASAL SPECT
PERFOR

First Aid

First Aid:INHALATION:REMOVE FROM EXPOSURE,RESTORE BREATHING. CONSULT
PHYSICIAN. SKIN:WASH WITH SOAP AND WATER,REMOVE CONTAMINATED
CLOTHING. EYE:FLUSH WITH WATER 15 MINUTES.

Fire Fighting

Flash Point:100F/37C (PMCC)

Lower Limits:0.9

Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM

Fire Fighting Procedures:SELF-CONTAIN BREATH APP, WATER FOG TO COOL
EXPOSED CONTAINER

Unusual Fire/Explosion Hazard:WATER SPRAY MAY BE INEFFECTIVE.CLOSED
CONTAINERS MAY EXPLODE DUE TO PRESSURE BUILD UP.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND
REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions:STORE AWAY FROM HEAT & FLAME IN
ORIGINAL CONTAINER. USE APPROVED BONDING & GROUNDING PROCEDURES.
AVOID EYE/SKIN CONTACT & BREATH OF VAPOR & SPRAY MIST

Other Precautions:DO NOT APPLY TO ANY PLACE WHICH MAY BE CHEWED BY
CHILDREN,CONTAINS LEAD. DO NOT BRAZE,WELD OR FLAME CUT WITHOUT
PROPER VENTILATION OR RESP PROTECTION.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN.

Ventilation:LOCAL EXHAUST

Protective Gloves:REQUIRED

Eye Protection:SAFETY SPECTACLES

Other Protective Equipment:UNPERFORATED SIDESHIELDS ON GLASSES.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:178F/81C

Vapor Density:> 1

Evaporation Rate & Reference:Percent Volatiles by Volume:59.3

Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,CO*2,LEAD OXIDE FUME,CHROMATE FUME

Disposal

Waste Disposal Methods:COMPLY WITH LOCAL,STATE AND FEDERAL REGULATION.
DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.