

## **B69 R 19,C & M ENAMEL OSHA RED**

### **MSDS Number**

BCMCB

### **National Stock Number**

8010-00N006153

### **Product Name**

B69 R 19,C & M ENAMEL OSHA RED

### **Manufacturer**

THE SHERWIN WILLIAMS COMPANY

### **Product Identification**

Product ID:B69 R 19,C & M ENAMEL OSHA RED

MSDS Date:01/01/1985

FSC:8010

NIIN:00N006153

MSDS Number: BCMCB

### **Responsible Party**

THE SHERWIN-WILLIAMS COMPANY

101 PROSPECT AVE N W

CLEVELAND , OH 44115-1042

US

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: DO693

### **Contractor**

THE SHERWIN-WILLIAMS CO

CLEVELAND, OH 44115

US

216-566-2902

Cage: DO693

### **Ingredients**

CHROMIUM ION (CR 6+)

CAS: 18540-29-9

RTECS: GB6262000

Fraction By Weight: 1.03%

OSHA PELC, 0.1 MG/M3 (CRO3)

ACGIH TLV: 0.05 MG/M3 (CR);8990

LEAD (SARA III)

CAS: 7439-92-1

RTECS: OF7525000

Fraction By Weight: 5.31%

OSHA PEL0.05 MG/M3;1910.1025

ACGIH TLV: 0.15 MG/M3;DUST 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

PROPYLENE OXIDE (SARA III)

CAS: 75-56-9

RTECS: TZ2975000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: 20 PPM; 9293

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 30%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: DE3030000

Fraction By Weight: 10%

OSHA PEL100 PPM

## Hazards

Effects of Overexposure:VAPOR: ANESTHETIC,LIGHTHEADEDNESS,STAGGER  
GAIT,IRRIT OF RESP TRACT. EYE/SKIN: IRRITATION.

## First Aid

First Aid:EYE: FLUSH WITH WATER 15 MIN. SKIN: WASH WITH SOAP &  
WATER,REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE FROM  
EXPOSURE,RESTORE BREATHING,CONSULT PHYSICIAN.

## Fire Fighting

Flash Point:86F/30C (PMCC)

Lower Limits:0.7

Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL FOAM

Fire Fighting Procedures:SELF-CONTAIN BREATH APP,WATER FOG TO COOL  
EXPOSED CONTAINER.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN  
EXPOSED TO EXTREME HEAT.

## Accidental Release

Spill Release Procedures:SECURE SOURCES OF IGNITION,VENTILATE AND  
REMOVE WITH INERT ABSORBENT

## Handling

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES IN

ORIGINAL CONTAINERS. GROUND CONTAINERS WHEN POURING. USE WITH ADEQUATE VENT. KEEP AWAY FROM CHILDREN,CONTAINS LEAD  
Other Precautions:WEAR APPROVED RESP DEVICE WHEN SANDING,GRINDING,WELDING,BRAZING OR FLAME CUTTING. AVOID CONTACT WITH SKIN/EYES AND BREATHING VAPORS OR SPRAY MIST.

## Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.  
Ventilation:LOCAL EXHAUST  
Protective Gloves:REQUIRED  
Eye Protection:SAFETY SPECTACLES  
Other Protective Equipment:UNPERFORATED SIDE SHIELDS ON SPECTACLES  
Supplemental Safety and Health  
ADD INGRED: MINERAL SPIRITS,140 FLASH

## Chemical Properties

Boiling Pt:B.P. Text:94F/34C  
Vapor Density:>1  
Evaporation Rate & Reference:Percent Volatiles by Volume:66.8

## Stability

Stability Indicator/Materials to Avoid:YES  
Hazardous Decomposition Products:CO,CO\*2,OXIDES OF LEAD & CHROMIUM

## Disposal

Waste Disposal Methods:COMPLY WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.