

## **XYLOL**

### **MSDS Number**

BCMGG

### **National Stock Number**

6810-00N006216

### **Product Name**

XYLOL

### **Manufacturer**

COWMAN CAMPBELL PAINT CO

### **Product Identification**

Product ID:XYLOL

MSDS Date:01/01/1985

FSC:6810

NIIN:00N006216

MSDS Number: BCMGG

### **Responsible Party**

COWMAN-CAMPBELL PAINT CO

Emergency Phone: 206-783-8835

Cage: HO230

### **Contractor**

COWMAN-CAMPBELL PAINT CO

SEATTLE, WA 98107

US

Cage: HO230

### **Ingredients**

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

### **Hazards**

Effects of Overexposure:EYE/SKIN: IRRIT. VAPOR: CNS

DEPRESSION,COORDINATION LOSS,IMPAIR

JUDGEMENT,STUPOR,UNCONSCIOUSNESS

### **First Aid**

First Aid:INHALATION: REMOVE FROM EXPOSURE,GIVE ARTIF RESP IF  
NEEDED,CALL PHYSICIAN. EYE: FLUSH WITH WATER 15 MINUTES. SKIN: WASH  
WITH SOAP & WATER,REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT  
INDUCE VOMITIN G,CONSULT PHYSICIAN.

### **Fire Fighting**

Flash Point:81F/27C

Lower Limits:1.0

Extinguishing Media:DRY CHEMICAL,FOAM,FOG WATER SPRAY.

Fire Fighting Procedures:SELF-CONT BREATH APP,WATER FOG TO COOL EXPOSED

## CONTAINERS.

Unusual Fire/Explosion Hazard: LIQUIDS CAN RELEASE VAPORS THAT CAN READILY FORM FLAMMABLE MIXTURES.

## Accidental Release

Spill Release Procedures: SECURE IGNITION SOURCES. CONTAIN SPILLED LIQUID WITH SAND OR EARTH, RECOVER FREE LIQUID, ADD ABSORBENT TO AREA. AVOID BREATHING VAPORS, KEEP PEOPLE AWAY, VENTILATE AREA. KEEP PETROLEUM PRODUCTS OUT OF STREAMS & WATERWAYS.

## Handling

Handling and Storage Precautions: DO NOT STORE OR HANDLE NEAR SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT IN USE. GROUND CONTAINER WHEN POURING, AVOID FREE FALL IN EXCESS INCHES  
Other Precautions: AVOID REPEATED/PROLONGED SKIN/EYE CONTACT & BREATHING OF VAPORS. DO NOT WELD, FLAME CUT, BRAZE OR SMOKE IN AREA OF USE.

## Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.  
Ventilation: LOCAL/MECHANICAL WITH EXPLOSION PROOF MOTORS.  
Protective Gloves: CHEM RESISTANT  
Eye Protection: CHEM SPLASH GOGGLES  
Other Protective Equipment: CHEM RESISTANT APRON OR CLOTHING TO PREVENT SKIN CONTACT  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt: B.P. Text: 279F/137C  
Vapor Pres: 46  
Vapor Density: >1  
Evaporation Rate & Reference: >1 (ETHER)  
Percent Volatiles by Volume: 100

## Stability

Stability Indicator/Materials to Avoid: YES  
STRONG OXIDANTS LIKE LIQUID CHLORINE & CONCENTRATED OXYGEN.  
Hazardous Decomposition Products: CARBON MONOXIDE

## Disposal

Waste Disposal Methods: COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.