

# ALL-WEATHER, HIGH-HIDE TINT BASE, PAINT, 1149

•

#### **MSDS Number**

BCMHQ

#### **National Stock Number**

8010-00N006245

#### **Product Name**

ALL-WEATHER, HIGH-HIDE TINT BASE, PAINT, 1149

#### Manufacturer

DEVOE AND RAYNOLDS CO

# **Product Identification**

Product ID:ALL-WEATHER,HIGH-HIDE TINT BASE,PAINT,1149 MSDS Date:01/01/1985 FSC:8010 NIIN:00N006245 MSDS Number: BCMHQ

# **Responsible Party**

**DEVOE & RAYNOLDS CO** 

4000 DUPONT CIRCLE

LOUISVILLE , KY 40207-4802

US

Cage: EO559

# Contractor

GROW GROUP INC DEVOE AND REYNOLDS CO DIV

LOUISVILLE, KY 40207-4802

US

502-361-2536

Cage: 97758

#### Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 18.3%

OSHA PEL100 PPM

# Hazards

Effects of Overexposure:EYE/SKIN: IRRIT. VAPOR: IRRIT RESP TRACT,HEADACHE,DROWSINESS,DIZZY,NAUSEA,VOMITING.

# First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR,GIVE ARTIFICIAL RESPIRATION IF NEEDED,CONSULT PHYSICIAN. EYE: FLUSH WITH WATER 15 MINUTES,CALL PHYSICIAN. SKIN: WASH WITH SOAP & WATER,REMOVE CONTAMINATED CLOTHING.

# **Fire Fighting**

Flash Point:100F/37C Lower Limits:1.1 Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM



Fire Fighting Procedures:SELF-CONTAIN BREATH APP,WATER FOG TO COOL EXPOSED CONTAINERS Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE FROM PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT.

•

#### **Accidental Release**

Spill Release Procedures:SECURE IGNITION SOURCES. SOAK UP SPILL ON SAWDUST OR OTHER ABSORBENT SOLID AND STORE IN A METAL CONTAINER UNTIL PROPERLY DISPOSED.

#### Handling

Handling and Storage Precautions:STORE AWAY FROM HIGH TEMPERATURE SOURCES & ELIMINATE ALL IGNITION SOURCES IN STORAGE AREA. Other Precautions:PROMPTLY DISPOSE OF RAGS OR OTHER COMBUSTIBLE ABSORBENTS USED TO CLEAN UP SPILLS. STORE PAINT-SOAKED RAGS,TEMPORARILY,IN CLOSED METAL CONTAINERS TO PREVENT SPONTANEOUS COMBUSTION.

# **Exposure Controls**

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN. Ventilation:LOCAL EXHAUST Eye Protection:SAFETY GOGGLES. Supplemental Safety and Health

# **Chemical Properties**

Boiling Pt:B.P. Text:310F/154C Vapor Density:>1 Evaporation Rate & Reference:Percent Volatiles by Volume:34.9

# Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:HEAT,SPARKS & FIRE

#### Disposal

Waste Disposal Methods:BY METHODS CONSISTENT WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.