

HIGH TEMPERATURE WEAR RESISTANT PUTTY RESIN

•

MSDS Number

BCNPW

National Stock Number

8030-00N006795

Product Name

HIGH TEMPERATURE WEAR RESISTANT PUTTY RESIN

Manufacturer

DEVCON

Product Identification

Product ID: HIGH TEMPERATURE WEAR RESISTANT PUTTY RESIN MSDS Date: 01/01/1987 FSC:8030 NIIN:00N006795

MSDS Number: BCNPW **Responsible Party**

DEVCON

Emergency Phone: 617 777 1100

Cage: 16059 **Contractor**

DEVCON CORP

DANVERS, MA 01923-3753

US

1-508-777-1100 Cage: 16059

Ingredients

GRAPHITE (CAS# 7782-42-5) (TLV IS RESPIRABLE DUST)

RTECS: VV7780000

ACGIH TLV: 2.5 MG/CUM

Hazards

Effects of Overexposure: EYE IRRIT. PRLNG &/OR RPTD SKIN CONT POSS IRRIT & SENSITIZATION.

First Aid

First Aid:EYES:FLUSH W/PLENTY OF CLEAR H*20 FOR @ LEAST 15 MIN.CALL DR. SKIN:RMV W/WARM SOAPY H*20. INHAL:RMV PERSON TO FRESH AIR.

Fire Fighting

Flash Point: 400F, TOC

Extinguishing Media: CO*2/DRY CHEM, POLYMER FOAMS FOR LARGE FIRES.

Fire Fighting Procedures: AVOID BREATHING SMOKE.

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures: PREVENT SKIN & EYE CONT. SCRAPE UP & DISPOSE OF IN SUITABLE CNTNRS.USE ABSORBENT COMPOUND IF NECESSARY. WASH SPILL AREA W/INDSTRIAL CLEANING AGENT.

Handling



Handling and Storage Precautions: USE W/ADEQUATE VENT.AVOID SKIN CONT.PVNT EYE CONT.STORE IN COOL, DRY PLACE. HANDLE IAW HAZ POTENTIALITIES OF CURING AGENT WHEN MIXED THEREWITH. Other Precautions: WASH THOROUGHLY AFTER USING.

Exposure Controls

Respiratory Protection: NONE IN NORMAL USE UNLESS IN CONFINED AREA OR W/OTHR MATL REQ PROT.

Ventilation: GOOD GENL VENT.LOCAL EXH RECOMND FOR PRLNG/FREQUENT USE.

Protective Gloves: RUB/DISPOSABLE

Eye Protection: SFTY GLASSES W/SIDE SHLDS

Supplemental Safety and Health PRODUCT DISCONTINUED 1985.

Chemical Properties

Vapor Pres:0 Spec Gravity:2.1 Solubility in Water:NIL Appearance and Odor:DARK GRAY PASTE,LOW ODOR. Percent Volatiles by Volume:0

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:OPEN FLAME/EXCESSIVE HEAT. Hazardous Decomposition Products:OXIDES OF CARBON,ALDEHYDES,ACIDS Conditions to Avoid Polymerization:HT GENERATED IF MIX W/EPOXY HARDNER.CAUTION IF MIX LGE QUANT

Disposal

Waste Disposal Methods: DISPOSE OF IAW FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.