

PRIMER,PAINT,ZINC-CHROMATE ALKYD TYPE

MSDS Number

BCNXZ

National Stock Number

8010-00N006932

Product Name

PRIMER,PAINT,ZINC-CHROMATE ALKYD TYPE

Manufacturer

S L GILLMAN PAINT COMPANY

Product Identification

Product ID:PRIMER,PAINT,ZINC-CHROMATE ALKYD TYPE

MSDS Date:01/01/1987

FSC:8010

NIIN:00N006932

MSDS Number: BCNXZ

Responsible Party

S.L. GILLMAN PAINT COMPANY

Emergency Phone: 404 622 1326

Cage: 00269

Contractor

S.L. GILLMAN PAINT COMPANY

ATLANTA

404 622 1326

Cage: 00269

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

OSHA PEL100 PPM

CHROMIUM (VI) OXIDE

CAS: 1333-82-0

RTECS: GB6650000

OSHA PELC, 0.1 MG/M3 (CRO3)

ACGIH TLV: 0.05 MG/M3(CR); 8990

(ALC(FIBROUS))(NON-ASBESTOS FORM)(TLV IS RESPIRABLE DUST)

RTECS: VV7720000

ACGIH TLV: 2 MG/CUM

ZINC OXIDE

CAS: 1314-13-2

RTECS: ZH4810000

OSHA PEL15MG/M3 TDUST/5 FUME

ACGIH TLV: 10MG/M3 TDUST; 9293

Hazards

Effects of Overexposure:DIZZINESS,LIGHT-HEADED ,HEADACHE.ASTHMA
AGGRAVATED BY EXP

First Aid

First Aid:EYES:FLUSH THOROUGHLY W/H*2O FOR @ LEAST 15 MIN.GET MED
ATTN.SKIN:FLUSH THOROUGHLY W/H*2O.GET MED ATTN. INHAL:REMOVE FROM
EXPOSURE,GIVE O*2,GET MED ATTN. INGEST:DO NOT INDUCE VOMITING.GET
MED ATTN.

Fire Fighting

Flash Point:105F (40.6C),TCC
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:FOAM,CO*2,DRY CHEMICAL
Fire Fighting Procedures:WEAR SCBA.IF BURN-FUMES OF HCL,OXIDES OF
C,NITROGEN/SULFUR.
Unusual Fire/Explosion Hazard:H*2O UNSUITABLE AS EXT MEDIA;USE TO COOL
CONTNRS.AVOID SPREAD OF BURNING LIQ W/H*2O USED FOR COOLING

Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION.FLUSH SPILLS
AWAY W/H*2O.SMALL SPILLS MAY BE COLLECTED W/ABSORBENT MATERIALS.

Handling

Handling and Storage Precautions:MATL CLASSIFIED AS FLAMMABLE LIQ,KEEP
CNTNRS TIGHTLY COSED,COOL & AWAY FROM OPEN FLAMES & SPARKS.AVOID
EYE CONT,PRLNG SKIN CONT.
Other Precautions:AVOID INHAL OF HIGH CONCENTRATION OF VAPOR. HAZARDOUS
RESIDUE MAY REMAIN IN EMPTY CONTAINERS-DO NOT REUSE.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPRVD RESPIRATOR FOR ORGANIC VAPOR
Ventilation:MECH CLASS D EXPLOSION PROOF & LOCAL EXHAUST RECOMMENDED.
Protective Gloves:IMPERVIOUS RUB
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:IMPERVIOUS APRON.
Supplemental Safety and Health
COMPANY ADDRESS: 2250 MORELAND AVENUE, SE, ATLANTA, GA 30315.

Chemical Properties

Boiling Pt:B.P. Text:313-388F
Vapor Pres:2.0
Vapor Density:4.9
Spec Gravity:0.781
Solubility in Water:NEGLIGIBLE
Appearance and Odor:COLOR AS INDICATED ON LABEL, CHARACTERISIC ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS CAN CAUSE VIGOROUS REACTION
Stability Condition to Avoid:OPEN FLAMES/SPARKS.
Hazardous Decomposition Products:COMBUSTION CAN PRODUCE CO & CO*2.
Conditions to Avoid Polymerization:EXP OF VAP TO STRONG OXIDIZING
AGENTS,EXCESS HT/OPEN FLAMES.

Disposal

Waste Disposal Methods:OBSERVE ALL FEDERAL,STATE & LOCAL REGULATIONS IN
DISPOSL OF WASTE.DO NOT REUSE EMPTY CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.