

3011S ENAMEL PRIMER

MSDS Number

BCPLN

National Stock Number

8010-00N008120

Product Name

3011S ENAMEL PRIMER

Manufacturer

E I DU PONT DE NEMOURS AND CO (INC)

Product Identification

Product ID:3011S ENAMEL PRIMER

MSDS Date:01/01/1987

FSC:8010

NIIN:00N008120

MSDS Number: BCPLN

Responsible Party

E.I. DU PONT DE NEMOURS & CO. (INC.)

1007 MARKET ST BRANDYWINE BLDG 3332

WILMINGTON , DE 19898

US

Cage: 18773

Contractor

E.I. DU PONT DE NEMOURS & CO., INC.

WILMINGTON, DE 19898

US

800-441-3637

Cage: 18773

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

5MMHG

ACGIH TLV: 100 PPM (MFR)

5MMHG

ACGIH TLV: 50 PPM (MFR)

123-96-0) (OSHA PEL-0.05MG(PB)/CUM)

Hazards

Effects of Overexposure:INGEST:GI DISTRESS.INHAL:POSS NOSE&THROAT IRRIT.POSS NERVOUS SYS DEPRESSION CHARAC BY:(SEE OTHR PREC

First Aid

First Aid:INGEST:CALL PHYS IMMED,HAVE INGREDIENT NAMES AVAIL. INHAL:OF VAP/SPRAY MIST,REMOVE TO FRESH AIR.IF BREATHING DIFFICULTY PERSISTS/OCCURS LATER,CALL PHYS. EYE:IMMED FLUSH W/PLENTY H*2O @ LEAST 15 MIN;CA LL PHYS.SKIN:WASH W/SOAP&H*20;IRRIT OCCURS,CALL MD

Fire Fighting

Flash Point:20-73F,-7-23C;CC
Lower Limits:1.1%
Upper Limits:14%
Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL
Fire Fighting Procedures:FULL PROTECT EQUIP W/SCBA.COOL CLOSED CNTNRS W/H*20-FOG NOZZ
Unusual Fire/Explosion Hazard:HEAT >FLASH PT,EMITS FLAMM VAPS-MIX W/AIR,CAN BURN/EXPLO.FINE MIST/SPRAY POSS FLAMM @TEMPS

Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE SOURCES OF IGNITION. PREVENT SKIN CONTACT & BREATHING OF VAPOR. CONFINE & REMOVE W/INERT ABSORBANT.

Handling

Handling and Storage Precautions:OBSERVE LABEL PRECAUTNS.KEEP FROM HEAT,SPARKS,FLAME.CLOSE CNTNR AFT USE.GROUND CNTNRS WHEN POUR.WASH AFT HANDLE,BEFORE EAT/SMOKE.DONT STORE ABOVE 120F
Other
Precautions:HEADACHE,DIZZ,NAUS,STAGGER,CONFUSN,UNCONSCIOUS.PRLNG/RP TD SOLVNT OVEREXP ASSOC W/PERMANENT BRAIN&NERVOUS SYS DAMAGE.EYE:IRRIT/BURNING.SKIN:PRLNG/RPTD LIQ CONTACT-IRRIT W/DISCOMFORT&DERMATITIS.

Exposure Controls

Respiratory Protection:NIOSH/MSHA TC-23C APVD PAINT SPRAY RSPTR IF APPLY&UNTIL EXHAUST VAPS
Ventilation:SUFFICIENT IN VOLUME&PATTERN TO KEEP CONTAM REQUIRMNTS
Protective Gloves:NEOPRENE GLOVES
Eye Protection:W/SPLASH GUARDS/SIDESHLDs
Other Protective Equipment:COVERALLS RECOMMENDED
Supplemental Safety and Health
INGRED:ADVERSE EFFECT TO BLOOD FORM,NERV,URIN,REPROD SYS (EMBRYOTOX).SYMP-APPETITE LOSS,ANEMIA,SLEEP DISTURB,TIRED).ALSO ALKYD RESIN.PRECAU:NIOSH/MSHA APVD RSPTR/VENT IF SAND,FLM CUT,BRAZE,WELD

Chemical Properties

Boiling Pt:B.P. Text:129F-401F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:SLIGHT
Appearance and Odor:DENSITY:6.8-12.7 #/GALLON

Stability

Stability Indicator/Materials to Avoid: YES

NONE REASONABLY FORESEEABLE

Hazardous Decomposition Products: CO, C*2, SMOKE, OXIDES OF LEAD

Disposal

Waste Disposal Methods: DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS. INCINERATE ABSORBED MATERIAL IN ACCORDANCE W/FEDERAL, STATE & LOCAL REQUIREMENTS. DO NOT INCINERATE IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.