

WONDER WOODSTAIN, 9689 MAPLE

MSDS Number

BCPQK

National Stock Number

8010-00N008195

Product Name

WONDER WOODSTAIN, 9689 MAPLE

Manufacturer

DEVOE AND RAYNOLDS CO

Product Identification

Product ID:WONDER WOODSTAIN, 9689 MAPLE

MSDS Date:01/01/1987

FSC:8010

NIIN:00N008195

MSDS Number: BCPQK

Responsible Party

DEVOE & RAYNOLDS CO.

4000 DUPONT CIR

LOUISVILLE , KY 40207

US

Cage: EO559

Contractor

DEVOE AND RAYNOLDS CO DIV OF GROW GROUP INC

7600

LOUISVILLE, KY 40207

US

502-361-2536/502-589-9340

Cage: 6R552

Ingredients

AROMATIC NAPHTHA

Fraction By Weight: < 5%

IRON OXIDE

CAS: 1309-37-1

RTECS: NO7400000

Fraction By Weight: < 5%

OSHA PEL10 MG/M3 (FE)

ACGIH TLV: 5 MG/M3(FE),B2; 9293

MINERAL SPIRITS (CAS# 64742-88-7) (70-80%)

ACGIH TLV: 100 PPM (MFR)

Hazards

Effects of Overexposure: INHAL: RESP TRACT
IRRIT, HD, NAUS, DIZZY, FATIGUE, UNCONSCIOUS, RESP
ARREST. SKIN/EYE: IRRIT. (SEE SUPP DATA)

First Aid

First Aid: EYE: FLUSH W/ PLENTY OF H₂O FOR @ LEAST 15 MIN. SKIN: WASH
W/ SOAP, H₂O. REMOVE SOILED CLTHG. INHAL: RMV TO FRESH AIR. IF BRTHG
STOPS USE CPR. INGEST: DONT INDUCE VOMIT. ASPIRATION OF VOMIT CAN
CAUSE CHEM PNEUMO NITIS, POSS FATAL. IN ALL CASES, GET MED ATTN IMMED.

Fire Fighting

Flash Point: 102F (38.9C), SCC
Lower Limits: 1.0
Extinguishing Media: CO₂, DRY CHEM, FOAM/OTHR NFPA APPRVD METHOD FOR
CLASS B FIRE.
Fire Fighting Procedures: FULL PROT EQUIP, SCBA. USE H₂O TO COOL CLSD
CNTNRS, PVNT PRESS
Unusual Fire/Explosion Hazard: KEEP CNTNR CLSD TIGHT. ISOLATE FROM
HEAT, FLM. CLSD CNTNRS EXP TO EXT HEAT MAY EXPLO. (SEE OTHR PRECAUT)

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF
IGNITION (HEAT, FLAME). DONT SMOKE. AVOID BRTHG VAPORS. BEFORE CLEAN-UP
REFER TO HAZ CAUTION INFO IN OTHR SECTIONS. VENT AREA. CONTAIN SPILL
& REMOVE W/ INERT ABSORBENT, NON-SPARK TOOLS. S TORE IN CLOSED CNTNRS
UNTIL PROPERLY DISPOSED OF.

Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT. DONT
SMOKE. CONTINUOUS FRESH AIR FLOW TO PVNT VAP BUILDUP. DONT STORE
ABOVE 120F. KEEP CNTNR CLSD. DONT TRANSFER TO UNLABELLED CNTNRS.
Other Precautions: % VOLATILE BY VOL: 79.8-86.8. SPEC
GRAVITY: 0.823-0.868. UNUSUAL FIRE HAZ: DONT USE WELD/CUT TORCH
ON/NEAR CNTNR (EVEN EMPTY). IN EMER CONDTN, OVEREXP TO DECOMP PROD
HLTH HAZ. SYMP NOT IMMED. CALL DR.

Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED RESP PROT DEPENDING ON
CONDITION OF USE.
Ventilation: GENL DILUTION/LOCAL EXH VENT. RMV VAPOR FROM LOW LEVELS.
Protective Gloves: SLVT IMPERMEABL
Eye Protection: SFTY EYEWEAR W/ SIDE SHLDS
Other Protective Equipment: SOLVENT RESIST SFTY EYEWEAR, SOLVENT
IMPERMEABLE CLTHG, BOOTS.
Supplemental Safety and Health
OVEREXP: INGEST: STOMACH/INTESTINE IRRIT, NAUS, VOMIT, DIARR. PERM
BRAIN/NERVOUS SYS DMG ASSOC W/ RPTD, PRLNG SLVT OVEREXP. POSS LUNG
DUST DISEASE IF RPTD/PRLNG BRTHG OF SPRAY MIST/SAND DUST OVER YEARS

Chemical Properties

Boiling Pt: B.P. Text: 300-390F
Vapor Pres: 2.0
Vapor Density: > 1
Evaporation Rate & Reference: SLOWER THAN ETHER

Stability

Stability Indicator/Materials to Avoid: YES
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.
Hazardous Decomposition Products: MAY CAUSE HAZ FUMES WHEN HEATED TO
DECOMP-POSS CO₂

Disposal

Waste Disposal Methods: DISPOSE OF IAW FEDERAL, STATE & LOCAL
REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE
CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.