

INTERIOR/EXTERIOR ALKYD SEMI-GLOSS(SUP DATA

MSDS Number

BCTJF

National Stock Number

8010-00N009819

Product Name

INTERIOR/EXTERIOR ALKYD SEMI-GLOSS(SUP DATA

Manufacturer

AMERITONE PAINT CORP

Product Identification

Product ID:INTERIOR/EXTERIOR ALKYD SEMI-GLOSS(SUP DATA

MSDS Date:12/15/1987

FSC:8010

NIIN:00N009819

MSDS Number: BCTJF

Responsible Party

AMERITONE PAINT CORPORATION

18414 S.SANTA FE AVENUE

COMPTON , CA 90221

Emergency Phone: 213-639-6791

Info Phone: 213-639-6791

Cage: FO133

Contractor

AMERITONE PAINT CORP/COMPTON, CA 90221

190

LONG BEACH, CA 90801

US

310-639-6791

Cage: FO133

Ingredients

ALIPHATIC PETROLEUM DISTILLATE

Fraction By Weight: Fraction by Wt

OSHA PELOSHA PEL

ACGIH TLV: ACGIH TLV

MINERAL SPIRITS

CAS: 64742-88-7

Fraction By Weight: 18-24%

OSHA PELOSHA PEL

ACGIH TLV: ACGIH TLV

ODORLESS MINERAL SPIRITS

Fraction By Weight: 12-15%

OSHA PEL/OSHA PEL

ACGIH TLV: ACGIH TLV

AMORPHOUS SILICA

CAS: 7631-86-9

RTECS: VV7320000

Fraction By Weight: 23-32%

OSHA PEL80 MG/CUM/%SIO*2

ACGIH TLV: 0.1MG/M(TOTAL DUST)

Hazards

LD50 LC50 Mixture:

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Health Hazards Acute and Chronic:SEE SIGNS & SYMPTOMS OF OVEREXPOSURE.

Explanation of Carcinogenicity:N/A

Effects of Overexposure:INHAL:IRRIT OF RESP

TRACT,HDCH,NAUSEA,DIZZY,WEAK & FATIGUE.EXTREME EXPOS CAN

RESULT,UNCONSCIOUSNESS & EVEN RESP ARREST.SKIN/EYE:PRIMARY

IRRIT.INGEST:STOMACH/INTESTINAL IRRIT,NAUSEA,VOMIT,DIARRHEA.CHRO

NIC:RPTS ASSOC RPTD/PROLONG OCC OVEREXPTO SOLVENT W/ PERM BRAIN &

NERVOUS SYS DAMAGE.BREATH SPRAY/MIST SAND, (SUP DATA)

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE W/

SAFE HANDLING & USE INFORMATION.

First Aid

First Aid:INHAL:DIFFICULTY BREATHING,OBTAIN FRESH AIR.DIFFICULTY
CONTINUES SUMMON MED ASSIST IMMED.BREATH CEASES,RESTORE USING (PR
TECHNIQUES.SUMMON MED ASSIST.EYE:FLUSH W/ LG AMTS OF H*2O FOR AT
LEAST 15 MIN.G ET MED ASSIST.SKIN:WASH THOROUGHLY W/
SOAP/H*2O.REMOVE SOILED CLOTHING.GET MED ASSIST.IF IRRIT
PERSISTS.INGEST:DO NOT INDUCE VOMITING,CONSULT PHYSICIAN
IMMEDIATELY.

Fire Fighting

Flash Point Method:TCC

Flash Point:105F;40-56 C

Lower Limits:

Upper Limits:

Extinguishing Media:USE CO*2,DRY CHEMICAL FOAM OR OTHER NATIONAL FIRE
PROTECTION ASSOCIATION APPROVED METHOD FOR TREATING CLASS B FIRES.

Fire Fighting Procedures:SUMMON PROF FIREFIGHTERS.USE FULL PROT EQUIP
INCLUDING SCBA.H*2O SPRAY INEFFECTIVE.IF H*2O USED,FOG NOZZLES
PREFERRED.FIRE/HEAT.USE H*2O TO COOL CLOSED CONTRS.

Unusual Fire/Explosion Hazard:KEEP CONTR TIGHTLY CLOSED.ISOLATE FROM
HEAT/FLAME.CLOSED CONTR MAY EXPLODE.NEVER WELD/CUT TORCH NEAR
CONTRS.EMERGENCY OVEREXPOS TO DECOMP PROD MAY OTHER PRECAUT

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.DO NOT
SMOKE.AVOID BREATHING VAPORS.CONTAIN SPILLED MATERIAL.REMOVE W/
INERT ABSORBENT & NON SPARKING TOOLS.STORE IN CLOSED CONTAINER
UNTIL PROPERLY DISPOSED OF.

Neutralizing Agent:

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT & FLAME.DON'T
SMOKE.DO NOT STORE ABOVE 120 F.STORE LG QTY IN BLDG DESIGNED COMPLY
W/ OSHA1910.106.KEEP CONTR CLOSED WHEN(SUP DATA)

Other Precautions:KEEP OUT OF REACH OF CHILDREN.UNUSUAL FIRE &
EXPLOSION HAZ:CAUSE HEALTH HAZ.SYMP MAY NOT BE IMMEDIATELY
APPARENT.OBTAIN MEDICAL ATTENTION.VENT: SAFETY & HLTH STANDARDS IN
MIX,CURING AREAS.RMV SAND DUS T OF DRIED COAT.RMV VAPOR,LOWER

LEVELS.

Exposure Controls

Respiratory Protection:OUTDOOR/OPEN AREA W/ UNRSTR VENT:USE NIOSH/MSHA MECH FILTER.RSTR VENT:USE NIOSH/MSHA CHEM MECH FILTER CONFINED:USE NIOSH/MSHA AIR SUPPLY RESP HOODS.USE NIOSH/MSHA APPROV RESP FOR FLAME CUT,WELD,BRAZ,S AND OF MAT COATED W/ PROD.
Ventilation:PROVIDE GEN DILUTION OR LOCAL EXHST.VENT IN VOL & PATTERN TO KEEP AIR CONTAM CONC BELOW APPLICABLE(SEE OTHER PRECAUTION)
Protective Gloves:SOLVENT IMPERMEABLE.
Eye Protection:SOLVENT REST SAFETY EYEWEAR,SPLASH GDS.
Other Protective Equipment:SOLVENT IMPERMEABLE CLOTHING & BOOTS.
Work Hygienic Practices:REMOVE & WASH SOILED CLOTHING BEFORE REUSE.WASH HANDS BEFORE EATING,SMOKING OR USING THE WASHROOM.
Supplemental Safety and Health
PART NO:ENAMEL COLOR KEY DEEP TONE XA006BL BLUE.ACGIH TLV INGRED NO 4:5MG/CUM(RESP DUST)LB PER GL;9.29-10.01.VOC:361-380 GM/L.SIGNS SYMP OF OVEREXP:DUST FOR YRS MAY CAUSE DUST DISEASE OF LUNGS.HANDL S STORAGE PREC:NOT USED.DON'T TRANSFER CONTENTS TO BT OR OTHER UNLABLED CONTR.KEEP OUT OF REACH OF CHILDREN.

Chemical Properties

Boiling Pt:B.P. Text:315-390F
Melt/Freeze Pt:M.P/F.P Text:
Vapor Pres:
Vapor Density:HEAV > AIR
Spec Gravity:
pH:
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:
Appearance and Odor:
Percent Volatiles by Volume:49-52
Corrosion Rate:

Stability

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:
Hazardous Decomposition Products:MAY CAUSE HAZ.FUMES WHEN HEATED TO DECOMP FUMES MAY CONTAIN CARBON MONOXIDE,CARBON DIOXIDE.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/ LOCAL,STATE & FEDERAL REGULATIONS.INCINERATE ONLY IN APPROVED FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.