

## **INTERIOR/EXTERIOR ALKYD SEMI-GLOSS SUP DATA**

### **MSDS Number**

BCTJJ

### **National Stock Number**

8010-00N009822

### **Product Name**

INTERIOR/EXTERIOR ALKYD SEMI-GLOSS SUP DATA

### **Manufacturer**

AMERITONE PAINT CORP

### **Product Identification**

Product ID:INTERIOR/EXTERIOR ALKYD SEMI-GLOSS SUP DATA

MSDS Date:12/15/1987

FSC:8010

NIIN:00N009822

MSDS Number: BCTJJ

### **Responsible Party**

AMERITONE PAINT CORPORATION

18414 S. SANTA FE AVENUE

COMPTON , CA 90221

Emergency Phone: 213-639-6791

Info Phone: 213-639-6791

Cage: FO133

### **Contractor**

AMERITONE PAINT CORP/COMPTON, CA 90221

190

LONG BEACH, CA 90801

US

310-639-6791

Cage: FO133

### **Ingredients**

ALIPHATIC PETROLEUM DISTILLATE

Fraction By Weight: Fraction by Wt

OSHA PELOSHA PEL

ACGIH TLV: ACGIH TLV

MINERAL SPIRITS

CAS: 64742-88-7

Fraction By Weight: 18-24%

OSHA PELOSHA PEL

ACGIH TLV: ACGIH TLV

ODORLESS MINERAL SPIRITS

Fraction By Weight: 12-15%

OSHA PELN/K FP-N

ACGIH TLV: N/K FP-N

AMORPHOUS SILICA

CAS: 7631-86-9

RTECS: VV7320000

Fraction By Weight: 23-32%

OSHA PEL80 MG/CUM/%SIO\*2

ACGIH TLV: 0.1MG/M(TOTAL DUST)

## Hazards

LD50 LC50 Mixture:

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Health Hazards Acute and Chronic:SEE SIGNS & SYMPTOMS OF OVEREXPOSURE.

Explanation of Carcinogenicity:N/A

Effects of Overexposure:INHAL:IRRIT OF RESP.TRACT,HDCH,NAUSEA

DIZZY,WEAK,& FATIGUE,EXTREME EXPOS CAN RESULT,UNCONSCIOUSNESS & EVEN RESP.ARREST,SKIN/EYE:PRIMARY IRRIT.INGEST;STOMACH/INTESTINAL IRRIT RPTD/PROLONG OCC OVEREXP T O SOLVENT W/ PERM BRAIN & NERVOUS SYS DAMAGE.BREATH/MIST SAND, (SUP DATA)

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE W/ SAFE HANDLING & USE INFORMATION.

## First Aid

First Aid:INHAL:DIFFICULTY BREATHING.OBTAIN FRESH AIR.DIFFICULTY CONTINUES SUMMON MED ASSIST.IMMED.BREATH CEASES,RESTORE USING CPR TECHNIQUES.SUMMON MED ASSIST.EYEFLUSH W/ LG AMTS OF H\*2O FOR AT LEAST 15 MIN.GET MED ASSIST.SKIN:WASH THOROUGHLY W/ SOAP/H\*2O.REMOVE SOILED CLOTHING.GET MED ASSIST.IF IRRIT PERSISTS.INGEST.DO NOT INDUCE VOMITING.CONSULT PHYSICIAN IMMEDIATELY

## Fire Fighting

Flash Point Method:TCC

Flash Point:105 F;40-56 C.

Lower Limits:

Upper Limits:

Extinguishing Media:USE CO\*2,DRY CHEMICAL FOAM OR OTHER NATIONAL FIRE PROTECTION ASSOCIATION APPROVED METHODS FOR TREATING CLASS B FIRES

Fire Fighting Procedures:SUMMON PROF FIREFIGHTERS.USE FULL PROT EQUIP INCLUDING SCBA.H\*2O SPRAY INEFFECTIVE.IF H\*2O USED,FOG NOZZLES PREFERRED.FIRE/HEAT,USE H\*2O TO COOL CLOSED CONTRS

Unusual Fire/Explosion Hazard:KEEP CONTR TIGHTLY CLOSED.ISOLATE FROM HEAT/FLAME.CLOSED CONTR MAY EXPODE NEVER WELD/CUT TORCH WEAR CONTR.EMERGENCY OVEREXPOS .TO DECOMP.PROD MAY OTHER PRECAUT

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.DO NOT SMOKE.AVOID BREATHING.VAPORS.CONTAIN SPILLED MATERIAL.REMOVE W/ INERT ABSORBENT & NON SPARKING TOOLS.STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

Neutralizing Agent:

## Handling

Handling and Storage Precautions:KEEP FROM HEAT & FLAME,DON'T SMOKE, DO NOT STORE ABOVE 120 F.STORE LG QTY IN BLDG DESIGNED COMPLY W/ OSHA1910.106.KEEP CONTR CLOSED WHEN(SUP DATA)

Other Precautions:KEEP OUT OF REACH OF CHILDREN.UNUSUAL FIRE & EXPLOSION HAZ:CAUSE HEALTH HAZ.SYMP MAY NOT BE IMMEDIATELY APPARENT.OBTAIN MEDICAL ATTENTION,VENT;SAFETY & HLTH STANDARDS IN MIX,CURING AREAS.RMV SAND DUS T OF DRIED COAT.RMV VAPOR,LOWER LEVELS.

## Exposure Controls

Respiratory Protection:OUTDOOR/OPEN AREA W/ UNRSTR VENT:USE NIOSH/MSHA MECH FILTER.RSTR VENT:USE NIOSH/MSHA CHEM/ MECH FILTER CONFINED:USE NIOSH/MSHA AIR SUPPLY RESP HOODS.USE NIOSH/MSHA APPROV RESP FOR FLAME CUT,WELD,BRAZ, SAND OF MAT,COATED W/ PROD.  
Ventilation:PROVIDE GEN.DILUTION OR LOCAL EXHST.VENT IN VOL & PATTERN TO KEEP AIR CONTAM CONC BELOW APPLICABLE(SEE OTHER PRECAUTION)  
Protective Gloves:SOLVENT IMPERMEABLE  
Eye Protection:SOLVENT REST SAFETY EYEWEAR,SPLASH GDS  
Other Protective Equipment:SOLVENT IMPERMEABLE CLOTHING & BOOTS  
Work Hygienic Practices:REMOVE & WASH SOILED CLOTHING BEFORE REUSE.WASH HANDS BEFORE EATING,SMOKING OR USING THE WASHROOM  
Supplemental Safety and Health  
PART NO:ENAMEL COLOR KEY DEEP TONE XA009U - UMBER. ACGIH TLV INGRED NO 4:5MG/CUM(RESPIR DUST)LB.PER GL;9.29-10.01,VOC:361-380 GM/L.SIGNS SYMP OF OVEREXP;DUST FOR YRS MAY CAUSE DUST DISEASE OF LUNGS, HAN DL STORAGE PREC:NOT USED.DON'T TRANSFERCONTENTS TO BT OR OTHER UNLABELED CONTR.KEEP OUT OF REACH OF CHILDREN.

## Chemical Properties

Boiling Pt:B.P. Text:315-390 F  
Melt/Freeze Pt:M.P/F.P Text:  
Vapor Pres:  
Vapor Density:HEAV > AIR  
Spec Gravity:  
pH:  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:  
Appearance and Odor:  
Percent Volatiles by Volume:49-52  
Corrosion Rate:

## Stability

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:  
Hazardous Decomposition Products:MAY CAUSE HAZ.FUMES WHEN HEATED TO DECOMP.FUMES MAY CONTAIN CARBON MONOXIDE,CARBON DIOXIDE.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/ LOCAL,STATE & FEDERAL REGULATIONS.INCINERATE ONLY IN APPROVED FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.