

WONDER TONES INTERIOR LATEX FLAT WALL PAINT

MSDS Number

BCTJT

National Stock Number

8010-00N009831

Product Name

WONDER TONES INTERIOR LATEX FLAT WALL PAINT

Manufacturer

DEVOE AND RAYNOLDS CO

Product Identification

Product ID:WONDER TONES INTERIOR LATEX FLAT WALL PAINT

MSDS Date:07/19/1991

FSC:8010

NIIN:00N009831

MSDS Number: BCTJT

Responsible Party

DEVOE & RAYNOLDS CO

4000 DUPONT CIRCLE

LOUISVILLE , KY 40207

US

Emergency Phone: 502-589-9340; 303-623-5716

Info Phone: 502-589-9340

Cage: EO559

Contractor

DEVOE AND RAYNOLDS CO DIV OF GROW GROUP INC

7600

LOUISVILLE, KY 40207

US

502-361-2536/502-589-9340

Cage: 6R552

Ingredients

10 MG/M3 TDUST;2

CAS: 1332-58-7

RTECS: GF1670500

Fraction By Weight: < 5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 2 MG/M3 TDUST; 9293

SILICA, CRYSTALLINE - CRISTOBALITE

CAS: 14464-46-1

RTECS: VV7325000

Fraction By Weight: < 5%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.05 MG/M3 RDUST9293

ALUMINUM HYDROXIDE; (ALUMINA TRIHYDRATE)

CAS: 21645-51-2

RTECS: BD0940000

Fraction By Weight:

OSHA PEL15 MG/M3

ACGIH TLV: 10 MG/M3

SILICA, AMORPHOUS

CAS: 112926-00-8

Fraction By Weight: < 5%

OSHA PEL6 MG/M3

ACGIH TLV: 10 MG/M3 TDUST

1 @

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight: < 5%

1.67 LB/GAL.

RTECS: 9999999VO

Fraction By Weight: SEE ING

17 @ 68F.

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 45%

CALCIUM CARBONATE

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight:

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

POLYVINYL ACETATE ACRYLIC RESIN

Fraction By Weight: 10%

SILICA, CRYSTALLINE - QUARTZ

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: 10%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 10 - 15%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

3.2%

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 5%

OSHA PEL50 PPM, C

ACGIH TLV: 50 PPM, C VAP/MIST

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE:INHAL:IRRIT OF RESP TRACT; HDCH, DIZZ. SKIN/EYE CONT:MAY CAUSE IRRIT. INGEST:NO EFTS ANTIC FROM INGEST INCIDENTAL TO NORMAL USE. LGR QTYS MAY CAUSE DISTRESS OF DIGEST TRACT & NAUS. CHRONIC:PRLNG & RPTD BRTHG OF SPRAY MIST &/OR SANDING DUST OVER PERIOD OF YRS MAY CAUSE DUST DISEASE OF LUNGS. (EFTS OF OVEREXP)

Explanation of Carcinogenicity:CRYSTALLINE SILICA: GRP 2A, IARC VOL 7, P.341,1987; ANTIC TO BE CARCIN, NTP 6TH ANNUAL RPT ON CARCINOGENS, 1991. .

Effects of Overexposure:HTLH HAZ:CRYSTALLINE SILICA HAS BEEN CLASSIFIED AS PROB CARCIN FOR HUMANS BY IARC. EXCESS INHAL OF CRYSTALLINE SILICA IS ALSO KNOWN TO CAUSE SILICOSIS. (RISK DEPENDS ON DURATION & LEVEL OF EXPOS).

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE W/ SAFE HANDLING & USE INFORMATION.

First Aid

First Aid:INHAL:IF BRTHD, REMOVE TO FRESH AIR. EYE:FLUSH IMMED W/LG AMTS OF WATER FOR AT LST 15 MINS. CONSULT MD FOR MED TREATMENT. SKIN:REMOVE W/SOAP & WATER. REMOVE SOILED CLTHG. INGEST:DRINK 1 OR 2 GLASSES O F WATER TO DILUTE. DO NOT INDUCE VOMIT.CONSULT MD IMMED. TREAT SYMPTOMATICALLY. NEVER GIVE ANYTHING BY MOUTH TO UNCON PERSON.

Fire Fighting

Flash Point Method:SCC

Flash Point:NONE(MFR)

Lower Limits:SEE INGS

Extinguishing Media:USE CO*2, DRY CHEMICAL, FOAM OR OTHER NAT FIRE PROTECT ASSOCIATION APPROVED METHOD FOR TREATING A CLASS B FIRE.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP

. WATER SPRAY MAY BE INEFT; IF USED, FOG NOZZS PREF. WATER SHLD BE USED TO COOL CLSD CNTNR & PVNT (SUPDAT)
Unusual Fire/Explosion Hazard:CLSD CNTNR EXPOSED TO EXTREME HEAT MAY EXPLODE DUE TO PRESS BUILD-UP; OVEREXP TO DECOMP PROD MAY CAUSE HLTH HAZ. SYMP NOT IMMED APPARENT. OBTAIN MED ATTN.

Accidental Release

Spill Release Procedures:WASH W/WATER. CONTAIN SPILLED MATERIAL & REMOVE W/INERT ABSORBENT. STORE IN CLOSED CONTAINERS UNTIL PROPERLY DISPOSED OF. REFER TO HAZ CAUTIONS IN MSDS.

Neutralizing Agent:N/K

Handling

Handling and Storage Precautions:STORE BELOW 110 F.& KEEP FROM FREEZING.KEEP CONTAINER CLOSED WHEN NOT IN USE.DO NOT REUSE EMPTY CONTAINERS.KEEP OUT OF REACH OF CHILDREN.

Other Precautions:DO NOT BREATHE VAPORS/MISTS/DUSTS. USE ONLY W/ADEQUATE VENTILATION. DO NOT GET IN EYES.

Exposure Controls

Respiratory Protection:OUTDOOR/OPEN AREAS:SANDING, GRINDING, USE NIOSH/MSHA APPRVD MECH FILTER. RESTRICTED VENT:WEAR NIOSH/MSHA APPRVD CHEM/MECH FILTERS. CONFINED AREAS:NIOSH/MSHA APPRVD AIR SUPPLY RESP HOOD. USE NIOSH/MSHA APPRVD RESP WHEN FLAME CUTTING/(SUPDAT)

Ventilation:PROVIDE GEN DILUTION/LOC EXHST VENT IN VOL & PATTERN TO KEEP CONTAM CONC BELOW APPLIC SAFETY & HLTH STDS IN (SUPDAT)

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NOT REQUIRED.

Work Hygienic Practices:REMOVE & WASH SOILED CLOTHING BEFORE REUSE.WASH HANDS BEFORE EATING,SMOKING OR USING THE WASH ROOM.

Supplemental Safety and Health

MFR'S TRADE NAME/PART NO:HIGH HIDE BASE, 3649. VAP DENS:ING 1 LTR/WATER, OTHERS HVR. FIRE FIGHT:PRESS BUILD-UP. RESP PROT:WELDING/BRAZING/SANDING MATL COATED W/THIS PROD. FOLLOW MFR DIRECTIONS FOR USE . VENT:MIXING, APPLICATION & CURING AREAS & TO REMOVE SANDING DUSTS OF DRIED COATING & DECOMP PROD DURING (ING 13)

Chemical Properties

HCC:V7

Boiling Pt:B.P. Text:>212F,>100C

Melt/Freeze Pt:M.P/F.P Text:

Decomp Temp:Decomp Text:

Vapor Pres:SEE INGS

Vapor Density:SUPP DATA

Spec Gravity:

pH:

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:68

Corrosion Rate:

Stability

Stability Indicator/Materials to Avoid:YES

AVOID MATLS INCOMPATIBLE W/WATER.

Stability Condition to Avoid:

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF METALS LISTED IN INGREDIENTS SECTION.

Conditions to Avoid Polymerization:

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/ LOCAL,STATE AND FEDERAL REGS.INCINERATE ONLY IN APPROVED FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.