

INTERIOR/EXTERIOR ACRYLIC ENAMEL

MSDS Number

BCTLV

National Stock Number

8010-00N009875

Product Name

INTERIOR/EXTERIOR ACRYLIC ENAMEL

Manufacturer

AMERITONE PAINT CORP

Product Identification

Product ID:INTERIOR/EXTERIOR ACRYLIC ENAMEL

MSDS Date:11/18/1987

FSC:8010

NIIN:00N009875

MSDS Number: BCTLV

Responsible Party

AMERITONE PAINT CORPORATION

18414 S. SANTA FE AVENUE

COMPTON , CA 90221

Emergency Phone: 213-639-6791

Info Phone: 213-639-6791

Cage: FO133

Contractor

AMERITONE PAINT CORP/COMPTON, CA 90221

190

LONG BEACH, CA 90801

US

310-639-6791

Cage: FO133

Ingredients

PROPYLENE GLYCOL

CAS: 57-55-6

RTECS: TY2000000

Fraction By Weight: 5%

OSHA PELOSHA PEL

ACGIH TLV: ACGIH TLV

PHENYLMERCURIC ACETATE (SARA III)

CAS: 62-38-4

RTECS: OV6475000

Fraction By Weight:

OSHA PEL0.1 MG HG/M3;CEIL;S

ACGIH TLV: 0.01 MG HG/M3; 9192

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

ALUMINUM SILICATE

CAS: 1318-74-7

Fraction By Weight: 0-10%

OSHA PELOSHA PEL

ACGIH TLV: ACGIH TLV

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: < 1-5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

ESTER ALCOHOL

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight: < 5%

OSHA PELOSHA PEL

ACGIH TLV: ACGIH TLV

AQUA AMMONIA

CAS: 1336-21-6

RTECS: BQ9625800

Fraction By Weight: < 1%

OSHA PELOSHA PEL

ACGIH TLV: ACGIH TLV

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

LD50 LC50 Mixture:

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SEE SIGNS & SYMPTOMS OF OVEREXPOSURE.

Effects of Overexposure:ACUTE:BREATHING:IRRITATION OF THE RESPIRATORY

TRACT,HEADACHE,NAUSEA,DIZZINESS.SKIN OR EYE CONTACT:PRIMARY

IRRITATION.CHRONIC:PROLONGED & REPEATED BREATHING OF SPRAY MIST

&/OR SANDING DUST OVER A PERIO D OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE W/ SAFE HANDLING & USE INFORMATION (MFR).

First Aid

First Aid:INHAL:IF BREATHED,REMOVE TO FRESH AIR.EYES:FLUSH IMMEDIATELY W/ LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.CONSULT A

PHYSICIAN FOR MEDICAL TREATMENT.SKIN:REMOVE W/ SOAP & H*2O.REMOVE
SOILED CLOTHI NG.SWALLOWED:DRINK 1 OR 2 GLASSES OF H*2O TO DILUTE
DON'T INDUCE VOMITING.CONSULT PHYSICIAN IMMEDIATELY,TREAT
SYMPTOMATICALLY.

Fire Fighting

Flash Point:NONE

Lower Limits:

Upper Limits:

Extinguishing Media:CO*2,DRY CHEMICAL,FOAM OR OTHER(NFPN) APPROVED
METHOD FOR TREATING CLASS B FIRE.

Fire Fighting Procedures:SUMMON PROFESSIONAL FIREFIGHTER,USE FULL PROT
EQUIP INCLUDE SCBA.H*2O SPRAY MAY BE INEFFECTIVE.IF H*2O USED FOG
NOZZLES PREFERABLE.USE H*2O TO COOL CLOSED CONTR

Unusual Fire/Explosion Hazard:CLOSED CONTR EXPOSED TO EXTREME HEAT MAY
EXPLODE.OVEREXPOS TO DECOMP PRODS MAY CAUSE HEALTH HAZARD SYMPTOM
NOT IMMED APPARENT.OBTAIN MEDICAL ATTENTION.

Accidental Release

Spill Release Procedures:CONTAIN SPILLED MATERIAL & REMOVE WITH INERT
ABSORBENT.STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

Neutralizing Agent:

Handling

Handling and Storage Precautions:STORE BELOW 110 F AND KEEP FROM
FREEZING.KEEP CONTAINER CLOSED WHEN NOT IN USE.DO NOT REUSE EMPTY
CONTAINER DON'T TRANSFER CONTENT TO BOTTLES SUP DATA

Other Precautions:

Exposure Controls

Respiratory Protection:OUTDOOR/OPEN AREA SANDING/GRINDING USE
NIOSH/MSHA APPROVED MECH FILTERS.RESTRICT VENT.NIOSH/MSHA CHEM MECH
FILTER.CONFINED AREA NIOSH/MSHA APPRO AIR SUPPLY RESP/HOODS.USE
NIOSH/MSHA RESP WHEN FLAME CU T,BRAZ,ETC & SAND MAT COATED W/
PRODUCT

Ventilation:PROVIDE GEN DILUTION OR LOCAL EXHAUST TO KEEP AIR CONTAM
BELOW SAFETY & HEALTH STANDARDS.

Protective Gloves:NOT REQUIRED (MFR).

Eye Protection:SAFETY EYEWEAR W/ SPLASHGUARD/SIDESHIELD

Other Protective Equipment:NONE REQUIRED (MFR).

Work Hygienic Practices:REMOVE & WASH SOILED CLOTHING BEFORE REUSE.WASH
HANDS BEFORE EATING,SMOKING OR USING WASHROOM.

Supplemental Safety and Health

PART NO COLOR KEY DEEP TONE AE011R0 POUNDS PER GL9.0. PERCENT
VOLATILE:231GM/LITRE.HANDLING/STORAGE PRECAUTIONS:OR OTHER
UNLABELLED CONTAINERS.KEEP OUT OF REACH OF CHILDREN.

Chemical Properties

Boiling Pt:B.P. Text:212-369 F

Melt/Freeze Pt:M.P/F.P Text:

Decomp Temp:Decomp Text:

Vapor Density:LIGHT> AIR

Spec Gravity:

pH:

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:

Appearance and Odor:

Percent Volatiles by Volume:70

Corrosion Rate:

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:

Hazardous Decomposition Products:FUMES MAY CONTAIN CARBON
MONOXIDE,CARBON DIOXIDE,OXIDES OF NITROGEN.

Conditions to Avoid Polymerization:

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.INCINERATE ONLY IN APPROVED FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.