

## **EPIBOND 1210**

### **MSDS Number**

BCVNG

### **National Stock Number**

8040-00-023-7729

### **Product Name**

EPIBOND 1210

### **Manufacturer**

FURANE PRODUCTS M AND T CHEMICALS INC

### **Product Identification**

Product ID:EPIBOND 1210

MSDS Date:01/01/1985

FSC:8040

NIIN:00-023-7729

MSDS Number: BCVNG

### **Responsible Party**

FURANE PRODUCTS, M & T CHEMICALS, INC.

Emergency Phone: 213-247-6210

Cage: GO767

### **Contractor**

FURANE PRODUCTS, M & T CHEMICALS, INC.

LOS ANGELES, CA 90039-1011

US

818-247-6210/800-873-1138

Cage: GO767

### **Ingredients**

BIS A TYPE EPOXY RESIN;TLV UNKNOWN, BUT SPI ERF HAZARD

Fraction By Weight: 100%

### **Hazards**

Effects of Overexposure:SKIN IRRITANT; OTHER EFFECTS NOT NOTED, BUT AVOID EYE CONTACT OR INGEST.

### **First Aid**

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH, GET MEDICAL ATTENTION.

### **Fire Fighting**

Flash Point:COC >400F,>204C

Extinguishing Media:H\*2O,CO\*2, OR DRY CHEMICAL POWDER.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG APP H\*2O SPRAY TO COOL CONTR.

Unusual Fire/Explosion Hazard:MATL MAY/MAY NOT BURN. CONTAINER MAY EXPLODE IN HEAT OF FIRE.FIRE MAY YIELD TOXIC GASES.

### **Accidental Release**

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H\*2O SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W/COMMERCIAL ABSORBENT,SHOVEL INTO METAL DRUMS:LG SPILL:DI KE W COMMERCIAL

ABSORBENT,PUMP INTO COVERED DRUMS.

## Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:MAINTAIN STRICT HYGIENE, AVOID PHYSICAL CONTACT, REMOVE & WASH CONTAMINATED CLOTHING. MFG SUGGESTS USE OF PROTECTIVE SKIN CREAMS. EXHAUST CURING OVENS TO OPEN AIR. AVOID TEMPERATURE EXTREMES.

## Exposure Controls

Respiratory Protection:IF EXPOS TLV,NIOSH/MESA APPR SELF-CNTND BRTHG APP (POS PR MODE)

Ventilation:MECHANICAL (GENERAL/LOCAL EXHAUST)

Protective Gloves:PV/RUBBER

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

MFG LITERATURE SPECIFIES CATALYST AS EPOCAST 9615(NOT INCLUDED WITH THIS NSN, PER ITEM DESCRIPTION:SEE NSN 8040-00-084-4338 FOR CATALYST MSDS & TDS). THIS NSN IS FOR BASE ONLY.

## Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:DECOMPOSES

Spec Gravity:1.25

Solubility in Water:NEGLIGIBLE

Appearance and Odor:THICK GREY PASTE; ODOR NOT SPECIFIED.

Percent Volatiles by Volume:0

## Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HEAT, IGNITION SOURCES

Hazardous Decomposition Products:NONE NOTED, BUT EXPECT CO, CO\*2, H\*2O.

## Disposal

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL. HANDLE AND DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE AND LOCAL REGULATIONS. MFG SUGGESTS INCINERATION OR BURY IN APPROVED LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.