787455 LACQUER CAMOUFLAGE LIGHT GREEN 24300

MSDS Number

BCVXD

National Stock Number

8010-00-042-8899

Product Name

787455 LACQUER CAMOUFLAGE LIGHT GREEN 24300

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:787455 LACQUER CAMOUFLAGE LIGHT GREEN 24300 MSDS Date:01/01/1985

FSC:8010

NIIN:00-042-8899 MSDS Number: BCVXD

Responsible Party

PRATT AND LAMBERT INC

16116 E 13TH ST

WICHITA, KS 67201

US

Emergency Phone: 716-873-6000 DOT EMER 8002553924

Info Phone: 316-733-1361

Cage: 61196 **Contractor**

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000 Fraction By Weight: OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293 EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOBUTYL ACETATE RTECS: NP9100000 Fraction By Weight: 15%



ACGIH TLV: 150 PPM

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000 Fraction By Weight:

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 8%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:INHAL:ANEST,IRRIT OF RESPIRATORY TRACT OR ACUT NERV SYS DEPRRES,DHACH,DIZZ,STAGGERING GAIT,COMA,UNCO

First Aid

First Aid:IN CSE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATR WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.

Fire Fighting

Flash Point:44F TCC 7C TCC

Extinguishing Media:CO*2,DRY CHEM OR ALCOH FOAM.POLYMR PREF F/LG FIRES. Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAIL F/FIREMEN

Unusual Fire/Explosion Hazard: KP CONTNRS TIGHTLY CLOS. ISOLATE FR HEAT, ELECTRICAL EOPMT, SPARKS & OPN FLAME. CLOS CONTNRS MAY EX(SUP)

Accidental Release

Spill Release Procedures: REMOV ALL SOURCES OF IGNIT (FLAMES, HOT SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARK). AVOID BREATHING VAPORS. VENTILATE AREA. REMOV W/INERT ABSORBENT, & NON-SPARKING TOOLS.

Handling



Handling and Storage Precautions: DO NOT STORE ABOVE 120F STORE LG QUANTITIES IN BLDG DESIGNED TO COMPLY W/OSHA 1910.106.

Other Precautions: CONTAINERS SHLD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO NOT FLAM CUT, BRAS OR WELD COATED MATRLW/O BUR OF MNES APPRVD RESPIR OR APPROP VENTIL. AD LABL WRN

Exposure Controls

Respiratory Protection:OUTDR/OPN AREA, USE BUR. OF MNES APPRVD

MECHANICAL FILTR RESPIRATOR.

Ventilation: PROVID GEN DILUT OR LOC EXHAUST VENTIL TO KP TLV BELO

ACCEPT

Protective Gloves: F/PROLNG/REPEAT

Eye Protection: SAFETY EYEWR AGNST SPLASH

Other Protective Equipment: PREVNT PROLNGED SKIN CONTACT TO CONTAMINATED

CLOTHING.

Supplemental Safety and Health

UNUS FIRE/EXPLOS HAZ:PLODE WHN EXPOSED TO EXTREME HEAT.DO NOT EXPOSE TO

EXTREME HEAT.DO NOT EXPOSE TO VERY HOT SURFACES.

Chemical Properties

HCC:F2

Boiling Pt:B.P. Text:223-287F

Evaporation Rate & Reference: SLOWER THAN ETHER.

Percent Volatiles by Volume:72

Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES.

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/LOC, STATE & FEDERAL REGULATIONS. INCINERATE IN APPRVD FACILITY. DO NOT INCINERATE CLOSE CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.