

## **FA3654**

# **MSDS Number**

**BCWLQ** 

# **National Stock Number**

5915-00-057-3349

#### **Product Name**

FA3654

#### Manufacturer

FILTRON CO INC

### **Product Identification**

Product ID:FA3654 MSDS Date:01/01/1987 FSC:5915 NIIN:00-057-3349 MSDS Number: BCWLQ

# **Responsible Party**

FILTRON CO INC

148 SWEET HOLLOW RD

OLD BETHPAGE, NY 11804-1315

US

Emergency Phone: NONE

Cage: 81831

# Contractor

FILTRON CO INC

OLD BETHPAGE, NY 11804-1315

US

914-699-2000 Cage: 81831

# **Ingredients**

POLYCHLORINATED BIPHENYLS (PCBS) (SARA III)

CAS: 1336-36-3 RTECS: TQ1350000 Fraction By Weight: N//K

EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

### **Hazards**

Effects of Overexposure:INHAL:RESP TK IRRIT; SKIN/EYE;IRRIT,INFLAM,CHLORACNE, MAY CAUSE LIVER DAMAGE.

#### First Aid

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG,GIVE CPR, IF BRTHNG DIFF,GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP&WATER. RMV CONTAM CLTHNG&SHOES. INGEST:INDUCE VOMIT. RPT UNTIL VOMIT IS CLEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN

# Fire Fighting



Flash Point: NONE

Extinguishing Media: EXTINQUISH W. AGENT SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures: WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD BRTHG APP.

Unusual Fire/Explosion Hazard: MATL IS NON-FLAMMABLE BUT MAY GENERATE TOXIC GASES IN HEAT OF FIRE

#### **Accidental Release**

Spill Release Procedures: EVAC NON-ESSENTL PERSONNEL. VENT SPIL AREA. WEAR PROTECT EQUIPT. STOP LEAK. SOAK UP LIQUID W/NON-REACTIVE MATL (SAND, DIRT, ETC) OR RMV BY DIKE & PUMPING OR OTHER SUITABLE MEANS. CLEAN AREA W/SUITABLE SAFETY SOLVENT. LAUNDER CONTAMINATED CLTHNG.

#### Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions: CHLORODIPHENYLS MAY ATTACK SOME TYPES OF RUBBER AND PLASTIC. DO NOT USE CONTAMINATED WORK CLOTHING. WASH/SHOWER AFTER EXPOSURE TO PCB'S.

#### **Exposure Controls**

Respiratory Protection: NIOSH/MESA APPR SCBA/AIR SUPP RESPIR.

Ventilation: LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves: IMPERVIOUS

Eye Protection: GOGGLES/FACE SHIELD

Other Protective Equipment: WEAR FULL PROTECTIVE CLOTHING.

Supplemental Safety and Health

OVEREXPOS:CAN CAUSE FORMATION OF CYSTS.CAUSES STILLBIRTHS.IRRITATES

EYES, NOSE, THROAT.

### **Chemical Properties**

HCC:Z3

Solubility in Water: NEGLIGIBLE

Appearance and Odor: PALE YELLOW VISCOUS LIQUID W/HYDROCARBON ODOR

# **Stability**

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:SEE OTHER PRECAUTIONS Hazardous Decomposition Products:HYDROGEN CHLORIDE, CO, & OTHER TOXIC/IRRITATING GASES/FUMES.

#### Disposal

Waste Disposal Methods: CONTROLLED DISPOSAL REQD. GEN. V.HIGH TEMP INCINERATION. IAW ALL LOCAL, STATE, & FEDERAL REGULATIONS. PERMITTED DISPOSAL OPERATOR REQUIRED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.