

PR-1201-Q

MSDS Number

BCWNT

National Stock Number

5970-00-058-8887

Product Name

PR-1201-Q

Manufacturer

PRODUCTS RESEARCH AND CHEMICAL CORP

Product Identification

Product ID:PR-1201-Q
MSDS Date:01/01/1985
FSC:5970
NIIN:00-058-8887
MSDS Number: BCWNT

Responsible Party

PRODUCTS RESEARCH & CHEMICAL CORP.

5430 SAN FERNANDO ROAD

GLENDALE , CA 91209

US

Emergency Phone: 818-240-2060

Info Phone: 818-240-2060

Cage: DO563

Contractor

PRODUCTS RESEARCH & CHEMICAL

1800

GLENDALE, CA 91209

US

818-240-2060

Cage: DO563

Ingredients

LEAD PEROXIDE (LEAD DIOXIDE), (OSHA PEL FROM 29CFR

CAS: 1309-60-0

RTECS: OG0700000

Fraction By Weight: 7.0%

OSHA PEL0.05 MG/M3 (PB)

ACGIH TLV: 0.15 MG/M3(PB); 8990

Hazards

Effects of Overexposure:ACCELERATOR CONTAINS LEAD COMPOUND WHICH MAY BE
ABSORBED THROUGH BREAKS IN SKIN.

First Aid

First Aid:SKIN:WASH THOROUGHLY WITH SOAP AND WATER.EYES:FLUSH
THOROUGHLY WITH LARGE AMOUNTS OF WATER.INGESTION;INDUCE
VOMITING.INHALATION;REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF

NECESSARY.GET MEDICAL ATTENTION.

Fire Fighting

Flash Point:>200F PMCC

Lower Limits:1.7

Upper Limits:7.0

Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE

Fire Fighting Procedures:WEAR AIR-SUPPLIED RESPIRATOR WHILE FIGHTING FIRES.

Unusual Fire/Explosion Hazard:EMISSION OF TOXIC VAPORS.

Accidental Release

Spill Release Procedures:STOP LEAK AT SOURCE.ELIMINATE IGNITION SOURCES.ABSORB EXCESS WITH RAGS,PAPER TOWELS OR OTHER ABSORBENT MATERIAL.CLEAN AREA WITH XYLENE OR TOLUENE.PLACE IN CLOSED CONTAINERS.

Handling

Handling and Storage Precautions:KEEP IN CLOSED CONTAINERS AT ROOM TEMPERATURE.AVOID FIRE HAZARDS.PROTECT FROM PHYSICAL DAMAGE.AVOID ACCELERATOR SPILLAGE.

Exposure Controls

Respiratory Protection:AIR SUPPLIED RESPIRATOR RECOMMENDED IN CONFINED AREAS.

Ventilation:MECHANICAL/LOCAL EXHAUST.TO MINIMIZE SOLVENT VAPOR BELOW TLV

Protective Gloves:POLYETHYLENE

Eye Protection:CHEM GOGGLES

Other Protective Equipment:USE PROTECTIVE HAND CREAM

Supplemental Safety and Health

Chemical Properties

HCC:D1

Spec Gravity:1.7

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PINKISH-BROWN SYRUP;SLIGHT TOLUENE ODOR

Percent Volatiles by Volume:UNK

Stability

Stability Indicator/Materials to Avoid:YES

DECOMPOSES WHEN EXPOSED TO STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID IGNITION SOURCES

Hazardous Decomposition Products:OXIDES OF SULFUR;HYDROGEN SULFIDE;FORMIC ACID

Disposal

Waste Disposal Methods:PLACE ABSORBED MATL IN CLOSED CONTAINERS AND DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.DO NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.