

## **794420 GREEN 34102 1GL**

### **MSDS Number**

BCXFP

### **National Stock Number**

8010-00-068-8783

### **Product Name**

794420 GREEN 34102 1GL

### **Manufacturer**

PRATT AND LAMBERT

### **Product Identification**

Product ID:794420 GREEN 34102 1GL

MSDS Date:01/01/1985

FSC:8010

NIIN:00-068-8783

MSDS Number: BCXFP

### **Responsible Party**

PRATT AND LAMBERT

16116 E 13TH ST

WICHITA , KS 67201

US

Cage: 61196

### **Contractor**

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

### **Ingredients**

CYCLOHEXANOL

CAS: 108-93-0

RTECS: GV7875000

Fraction By Weight: 15%

OSHA PELS, 50 PPM

ACGIH TLV: S, 50 PPM; 9192

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 1.5%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM/300STEL;9394

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 7.5%

OSHA PEL200 PPM; Z-2

ACGIH TLV: S, 50 PPM; 9394

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight:

ACGIH TLV: 500 PPM

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: >5%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

## Hazards

Effects of Overexposure:INHALATION.ANESTHETIC,IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION

## First Aid

First Aid:CONTACT-FLUSH SKIN AND EYES WITH WATER WHILE REMOVING CONTAMINATED CLOTHING. INHALATION-REMOVE TO FRESH AIR. CALL PHYSICIAN IF SYMPTOMS PERSIST.

## Fire Fighting

Flash Point:21F 6C

Extinguishing Media:NFPA CLASS B EXTINGUISHER; POLYMER FOAM FOR LARGE FIRES

Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS VENTILATE AREA REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F STORE LARGE QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106

Other Precautions:GROULD CONTAINERS WHEN POORING-AVOID FREE FALL OF LIQUID IN XS OF FEW INCHES DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL WITHOUT BUR OF MINES APPROVED RESPIRATOR OR APPROPRIATE

VENTILATION.

## Exposure Controls

Respiratory Protection:OPEN AREA BUR MINES MECH RESPIRATOR-CLOSED-BUR MINES CHEM/MECH FILTE

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST TO KEEP TLV BELOW LIMIT

Protective Gloves:REG IF LONG CON

Eye Protection:TO PROTECT VS SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Supplemental Safety and Health

## Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:174-329F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER/ETHER

Percent Volatiles by Volume:66

## Stability

Stability Indicator/Materials to Avoid:YES

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS-INCINERATE IN APPROVED FACILITY-DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.