

DRO75-CONCENTRATE

MSDS Number

BCXQW

National Stock Number

8010-00-079-3758

Product Name

DRO75-CONCENTRATE

Manufacturer

DEVOE AND RAYNOLDS CO INC

Product Identification

Product ID:DRO75-CONCENTRATE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-079-3758

MSDS Number: BCXQW

Responsible Party

DEVOE & RAYNOLDS CO INC

Emergency Phone: 714-686-6930

Cage: EO559

Contractor

DEVOE COATINGS CO DIV OF GROW GROUP INC

RIVERSIDE, CA 92507-2606

US

Cage: 70506

Ingredients

ALIPHATIC NAPHTHA

Fraction By Weight: 22.0%

ACGIH TLV: 400 PPM

XYLENE SUBSTITUTE

Fraction By Weight: 56.0%

ACGIH TLV: 150 PPM

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 11.0%

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 5.0%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ALIPHATIC HTDROCARBONS

Fraction By Weight:

ACGIH TLV: 500 PPM

Hazards

Effects of Overexposure: INHALATION-HEADACHE, NAUSEA, DIZZINESS.
PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION.

First Aid

First Aid: INHALATION-HEADACHE, MOVE TO FRESH AIR. SKIN CONTACT-FLUSH
WITH LARGE AMOUNT OF WATER. REMOVE CONTAMINATED CLOTHING. EYE
CONTACT-FLUSH WITH CLEAN WATER FOR AT LEAST 15 MIN.-CALL PHYSICIAN.

Fire Fighting

Flash Point: 58 F-14.4 C PMCC

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS SHOULD BE
WORN BY FIREMEN

Unusual Fire/Explosion Hazard: USE WATER TO COOL CONTAINERS EXPOSED TO
FIRE

Accidental Release

Spill Release Procedures: AVOID BREATHING VAPORS, EXTINGUISH IGNITION
SOURCES IN AREA. AVOID CONTACT WITH LIQUID.

Handling

Handling and Storage Precautions: DO NOT STORE AT ELEVATED TEMPERATURES.

Other Precautions: CLOSE CONTAINERS AFTER USE

Exposure Controls

Respiratory Protection: IN CONFINED AREA USE U.S. BUR. OF MINES APPROVED
RESPIRATOR

Ventilation: LOCAL-SUFFICIENT TO KEEP CONCENTRATION BELOW GIVEN TLV

Protective Gloves: PROLONGED USE

Eye Protection: SOLVENT RESISTANT

Other Protective Equipment: NORMAL PROTECTIVE CLOTHING

Supplemental Safety and Health

BOILING POINT: 80-154.4 C HAZARDOUS

MAT'L: EO1400000 N-BUTYL ALCOHOL

Chemical Properties

HCC: V3

Boiling Pt: B.P. Text: 176-310 F

Vapor Density: > 1.0

Spec Gravity: 0.90

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: SLIGHT

Appearance and Odor: MOBILE LIQUID CONTAINING VOLATILE SOLVENTS. GREEN

Percent Volatiles by Volume: 75.3

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZING MATERIALS SOFTEN RUBBER
Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE

Disposal

Waste Disposal Methods: DISPOSE OF IN CLOSED CONTAINERS AWAY FROM
IGNITION SOURCES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.