

## **DRO72-CONCENTRATE**

### **MSDS Number**

BCXRW

### **National Stock Number**

8010-00-079-5437

### **Product Name**

DRO72-CONCENTRATE

### **Manufacturer**

DEVOE AND RAYNOLDS CO INC

### **Product Identification**

Product ID:DRO72-CONCENTRATE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-079-5437

MSDS Number: BCXRW

### **Responsible Party**

DEVOE & RAYNOLDS CO INC

Emergency Phone: 714-686-6930

Cage: EO559

### **Contractor**

DEVOE COATINGS CO DIV OF GROW GROUP INC

RIVERSIDE, CA 92507-2606

US

Cage: 70506

### **Ingredients**

ALIPHATIC NAPHTHA

Fraction By Weight: 20.0%

ACGIH TLV: 400 PPM

XYLENE SUBSTITUTE

Fraction By Weight: 72.0%

ACGIH TLV: 150 PPM

ALIPHATIC HYDROCARBONS

Fraction By Weight: 5.0%

ACGIH TLV: 500 PPM

TRIETHYLAMINE (SARA III)

CAS: 121-44-8

RTECS: YE0175000

Fraction By Weight:

OSHA PEL25 PPM/15 STEL

ACGIH TLV: 10 PPM/15 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight:

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Effects of Overexposure: INHALATION-HEADACHE, NAUSEA, DIZZINESS.  
PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION.

## First Aid

First Aid: INHALATION-MOVE TO FRESH AIR. SKIN CONTACT-FLUSH WITH LARGE AMOUNT OF WATER. REMOVE CONTAMINATED CLOTHING. EYE CONTACT-FLUSH WITH CLEAN WATER FOR AT LEAST 15 MIN.-CALL PHYSICIAN.

## Fire Fighting

Flash Point: 58 F-14.4 C PMCC

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN BY FIREMEN

Unusual Fire/Explosion Hazard: USE WATER TO COOL CONTAINERS EXPOSED TO FIRE

## Accidental Release

Spill Release Procedures: AVOID BREATHING VAPORS, EXTINGUISH IGNITION SOURCES IN AREA. AVOID CONTACT WITH LIQUID.

## Handling

Handling and Storage Precautions: DO NOT STORE AT ELEVATED TEMPERATURES

Other Precautions: CLOSE CONTAINERS AFTER USE

## Exposure Controls

Respiratory Protection: IN CONFINED AREA USE U.S. BUR. OF MINES APPROVED RESPIRATOR

Ventilation: LOCAL-SUFFICIENT TO KEEP CONCENTRATION BELOW GIVEN TLV

Protective Gloves: PROLONGED USE

Eye Protection: SOLVENT RESISTANT

Other Protective Equipment: NORMAL PROTECTIVE CLOTHING

Supplemental Safety and Health

BOILING POINT: 80-154.4C

## Chemical Properties

HCC: V3

Boiling Pt: B.P. Text: 176-310F

Vapor Density: >1

Spec Gravity: 0.98

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: SLIGHT

Appearance and Odor: BLACK MOBILE LIQUID CONTAINING VOLATILE SOLVENTS.

Percent Volatiles by Volume: 75.0

## Stability

Stability Indicator/Materials to Avoid: YES

OXIDIZING MATERIALS SOFTENS RUBBER

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

## **Disposal**

Waste Disposal Methods:DISPOSE OF IN CLOSED CONTAINERS AWAY FROM IGNITION SOURCES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.