

745406 ENAMEL ALKYD SG OLIVE DRAB 24087

MSDS Number

BCXVK

National Stock Number

8010-00-081-0809

Product Name

745406 ENAMEL ALKYD SG OLIVE DRAB 24087

Manufacturer

PRATT AND LAMBERT

Product Identification

Product ID:745406 ENAMEL ALKYD SG OLIVE DRAB 24087

MSDS Date:01/01/1985

FSC:8010

NIIN:00-081-0809

MSDS Number: BCXVK

Responsible Party

PRATT & LAMBERT

Emergency Phone: 316-733-1361

Cage: PRATT

Contractor

PRATT AND LAMBERT INC

2153

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

CAS: 7758-97-6

RTECS: GB2975000

Fraction By Weight: 8%

OSHA PEL0.05 MG/M3 (PB)

ACGIH TLV: 0.05MG/M3(CR)A2;8990

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 45%

ACGIH TLV: 500 PPM

LEAD NAPHTHENATE 36% LD 50 VALUE=.500 GMS/KG

Hazards

Effects of Overexposure: INAHL: ANEST IRRITATION OF RESPIRATORY TRACT OR ACUT NERV SYS DEPRSSN, HDACH, DIZZ, CONFUSN, UNCON, COMA.

First Aid

First Aid: IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A DR IF SYMPTOMS PERSIST.

Fire Fighting

Flash Point: 104F TCC 40C
Extinguishing Media: CO*2, DRY CHEM OR ALCOHOL FOAM. POLYMR FOAM RECOMM F/LG FIRES
Fire Fighting Procedures: SELF-CONTND BREATHING APPARAT WATR SPRAY MAY BE INEFFECTIVE
Unusual Fire/Explosion Hazard: KP CONTNRS TIGHTLY CLOS. ISOLAT FR HEAT, ELECTR EQUIPMT, SPARKS & OPN FLAME. CLOS CONTNRS MAY EXPLOD(SUP

Accidental Release

Spill Release Procedures: REMOV ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS.) AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F STORE LG QUANTITIES IN BLDG DESIGNED TO COMPLY W/OSHA 1910.106.
Other Precautions: CONTNRS SHLD BE GRNDED WHN POURNG. AVOID FRE FAL OF LIQD IN EXCESS OF FEW INCH. DO NOT FLAME CUT, BRAZ, WELD COATED MATRL W/O BUR MNES APRVD RESPIRT OR APPROP VENT. AD WARN LABL-DO NOT TAKE INTERNAL

Exposure Controls

Respiratory Protection: MECH FILTR RESPIRAT TO REMOV SOLID AIR BORNE PARTICL/OVERSPRAY INDOR
Ventilation: LOC EXHAUS VENTIL TO KP TLV OF HAZARD INGRED BELO ACCEP LIMT
Protective Gloves: F/PRLNG/REPEAT
Eye Protection: SAFTY EYEWEAR PROTECT AGN
Other Protective Equipment: PREVNT PRLNG SKIN CONTACT TO CONTAMINATED CLOTHING.
Supplemental Safety and Health
UNUS. FIRE/EXPLOS. HAZARDS: WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO VERY HOT SURFACES.

Chemical Properties

HCC: F4
Boiling Pt: B.P. Text: 311-373F
Evaporation Rate & Reference: SLOWER THAN ETHER
Percent Volatiles by Volume: 60

Stability

Stability Indicator/Materials to Avoid: YES
Stability Condition to Avoid: AVOID FIRES, HEAT, & HOT SURFACES.

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. INCINERATE IN APPRVD FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

