

## **792419 LAC ACRYLIC N/C**

### **MSDS Number**

BCXZX

### **National Stock Number**

8010-00-082-2479

### **Product Name**

792419 LAC ACRYLIC N/C

### **Manufacturer**

PRATT AND LAMBERT INC

### **Product Identification**

Product ID:792419 LAC ACRYLIC N/C

MSDS Date:01/01/1985

FSC:8010

NIIN:00-082-2479

MSDS Number: BCXZX

### **Responsible Party**

PRATT AND LAMBERT INC

16116 E 13TH ST

WICHITA , KS 67201

US

Emergency Phone: 716-873-6000 DOT EMER 8002553924

Info Phone: 316-733-1361

Cage: 61196

### **Contractor**

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

### **Ingredients**

ISOBUTYL ACETATE

RTECS: NP9100000

Fraction By Weight: 45%

ACGIH TLV: 150 PPM

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 15 - 20%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

CHROMIUM OXIDE

RTECS: GL6420000

Fraction By Weight:

METHYLETHYL KETONE

RTECS: PM7780000

Fraction By Weight:

ACGIH TLV: 200 PPM

LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

CAS: 7758-97-6

RTECS: GB2975000

Fraction By Weight:

OSHA PEL 0.05 MG/M3 (PB)

ACGIH TLV: 0.05MG/M3(CR)A2;8990

## Hazards

Effects of Overexposure: INHAL: ANESTH, IRRIT OF RESPIR TRACT, ACUTE NERV  
SYS DEPRESS, DHACH, DIZZ, CONFUS, UNCONSC OR COMA.

## First Aid

First Aid: IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE  
REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL  
A PHYSICIAN IF SYMPTOMS PERSIST.

## Fire Fighting

Flash Point: 21°F TCC -6°C

Lower Limits: 1.30

Extinguishing Media: MFPA CL B EXTING(CO\*2, DRY CHEM OR ALCOHOL  
FOAM) F/MFPA FIRES.

Fire Fighting Procedures: SELF CONTAINED BREATH APPARAT  
F/FIREMEN. WATER-COOL CLOS CON.

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS. ISOLAT  
F/HEAT, ELECTR EQPMT, SPARKS & OPEN FLAME. CLOS.

## Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT  
SURFACES, AND ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID  
BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON  
SPARKING TOOLS.

## Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120°F. STORE LARGE  
QUANTITIES IN BLDG DESIGNED TO COMPLY W/OSHA 1910.106.

Other Precautions: CONTNRS SHLD BE GROUNDED WHEN POURING. AVOID FREE FALL  
OF LIQD IN EXCESS OF FEW INCH. DO NOT FLAME CUT, BRAZE OR WELD COATED  
WATER OF BUR OF MINES APPRVD RESPIR OR APPROP VENT. AVOID DO NOT  
TKE INTE

## Exposure Controls

Respiratory Protection: OUTDOOR/OPEN AREAS, USE BUR OF MINES APPRVD MECH  
FILTER RESPIRAT.

Ventilation: GEN DILUT OR LOC EXHAUST VENT IN VOL TO KEEP TLV BELOW  
ACCEP

Protective Gloves: REQD F/REPEATED

Eye Protection: SAFETY EYEWEAR

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING.

Supplemental Safety and Health

## **Chemical Properties**

HCC:F2

## **Stability**

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRES, HEAT, & HOT SURFACES.

## **Disposal**

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/LOCAL, STATE, & FEDERAL  
REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED  
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.