

ENAMEL, ALKYD, CAMOUFL. SNAD

MSDS Number

BCZGC

National Stock Number

8010-00-111-8336

Product Name

ENAMEL, ALKYD, CAMOUFL. SNAD

Manufacturer

PRATT AND LAMBERT

Product Identification

Product ID: ENAMEL, ALKYD, CAMOUFL. SNAD MSDS Date:01/01/1987 FSC:8010 NIIN:00-111-8336

MSDS Number: BCZGC

Responsible Party

PRATT & LAMBERT

Emergency Phone: 316-733-1361

Cage: PRATT **Contractor**

PRATT AND LAMBERT INC

2153

US

CLEVELAND, OH 44101-1027

216-566-2902 Cage: 61196

Ingredients

*MINERAL SPIRITS CAS: 64475-85-0 RTECS: PY8240000

Fraction By Weight: 35% ACGIH TLV: 500PPM

*METHYL ETHYL KETOXIME

RTECS: PM7783000 Fraction By Weight:

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293 EPA Report Quantity: 5000 LBS



DOT Report Quantity: 5000 LBS

*XYLOL/ZYLENE (NIOSH SHOWN FOR *XYLOL)

RTECS: ZF1575000 Fraction By Weight: ACGIH TLV: 100PPM

TRIETHYLAMINE (SARA III)

CAS: 121-44-8
RTECS: YE0175000
Fraction By Weight:

OSHA PEL25 PPM/15 STEL

ACGIH TLV: 10 PPM/15 STEL; 9293 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure: INHAL: ANEST. IRRIT OF NOSE, THROAT, EYES & POSS

DIZZ.& NAUSEA.

First Aid

First Aid:INHAL:REMOV FR EXPOSR & PROVID FRESH AIR. SPLASH EYES:FLUSH IMMED.W/LG AMTS. OF WATR F/15 MIN. SLASH SKN-REMOV CONTAMINAT CLOTHNG & WASH ALL AFFECT AREA W/WATR. INGESTION:DO NOT INDUCE VOMITING.CALL A "DR" IMMED. IN AL CASES.

Fire Fighting

Flash Point: 104F TCC 40C T

Extinguishing Media: CARBON DIOXIDE, DRY CHEM, OR ALCOH FOAM. Fire Fighting Procedures: SELF-CONTND BREATHING APPARAT SHLD BE AVAIL F/FIREMEN.

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS. ISOLAT FR HEAT, ELECT EQPMT, SPARKS & OPN FLAME. CLOS CONTNRS MAY EXPLOD (SUP

Accidental Release

Spill Release Procedures: REMOV ALL SOURCES OFIGNIT (FLAMES, HOT SURFACES, & ELECTR, STATIC OR FRICTIONAL SPARKS). VENTILATE AREA & AVD BREATHING VAP.REMOV W/INERT ABSORBENT & NON-SPARKING TOOLS. STEPS MUST BE TAKEN TO PREVNT CO NTAM OF GROUND WATER OR STREAMS.

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F.STORE LG QTYS, IN COMPLIANCE W/OSHA 1910.106.CONTNRS SHLD BE GROUNDED & BONDED TO THE RECEIVING CONTAINER.

Other Precautions: DO NOT CUT OR WELD ON EMPTY CONTNR."DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

Exposure Controls

Respiratory Protection: USE NIOSH APPRVD MECH RESPIRAT. TO REMOV

OVERSPRAY WHN SPRA OUTDR OR

Ventilation: PROVID GEN DILUT OR LOC EXHAUSTVENT IN VOLM TO KEEP BELO

ACC

Protective Gloves:SOLVNT IMPERMEA Eye Protection:SAFETY EYEWEAR

Other Protective Equipment: PROTECTIVE EQPMT TO PRVNT SKIN CONTCT.

Supplemental Safety and Health



*INDICATES SOLVENT. UNUS.FIRE & EXPLOS.HAZARDS: WHN EXPOSED TO EXTREME HEAT.

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:311-373F

Vapor Density: HEAV

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 59

Stability

Stability Indicator/Materials to Avoid:YES
AVD CONTCT W/STRONG ACIDSOR AKALINE MATERIAL.
Stability Condition to Avoid:FIRES, HEAT & HOT SURFACES.
Hazardous Decomposition Products:BURNING W/PRODUCE SMOKE &OXIDES OF CARBON & LEAD
Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIV CHEMS
W/O TECHNICAL SUPERVISION

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/LOCAL, STATE, & FED. REGULATIONS. INCINERATE IN EPA APPRVD FACILITY. DO NOT INCINERATE CLOS CONTNRS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.