KRYLON INERIOR/EXTER ENAMEL AEROSOL 2105

MSDS Number

BDBBH

National Stock Number

8010-00-132-2864

Product Name

KRYLON INERIOR/EXTER ENAMEL AEROSOL 2105

Manufacturer

BORDEN INC KRYLON DEPARTMENT

Product Identification

Product ID:KRYLON INERIOR/EXTER ENAMEL AEROSOL 2105
MSDS Date:01/01/1985
FSC:8010
NIIN:00-132-2864
MSDS Number: BDBBH

Responsible Party

BORDEN INC., KRYLON DEPARTMENT

630 E WASHINGTON

NORRISTOWN , PA 19404

US

Cage: EO688

Contractor

KRYLON PRODUCTS

SOLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

Ingredients

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 25%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 15%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIANT; 9192

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 10%

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 5 - 10%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 3%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

Hazards

Effects of Overexposure:DIZZY, CONFUSION,WEAKNESS.

First Aid

First Aid:INHALATION:REMOVE TO FESH AIR. IF SPRAYED IN EYES, WASH W/WATER 15 MINUTES. SEE A DR.

Fire Fighting

Extinguishing Media:CO,CO2,FOAM, DRY CHEMICAL
Fire Fighting Procedures:WATER FOG TO COOL CANS TO PREVENT EXPOSURE TO HIGH TEMPS
Unusual Fire/Explosion Hazard:FLAME FRONT IF SPRAYED DIRECTLY AT A OPEN FLAME. CANS MAY BURST WITH VIOLENCE WHEN EXPOSED TO HEAT.

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION SOAK UP WITH ABSORBENT MATERIAL. VENTILATE AREA.

Handling

Handling and Storage Precautions:DO NOT STORE AT TEMPS OVER 120F. AVOID RADIATORS, STOVES, DIRECT SUNLIGHT OR OTHER HEAT SOURCE. HIGH TEMP MAY CAUSE BURSTING.
Other Precautions:AVOID PUNCTURING IF SPRAY IS BURNED DO NOT BREATH IRRITATING OR TOXIC FUMES.

Exposure Controls

Respiratory Protection:NOT REQUIRED WITH ADEQUAT VENTILATION
Ventilation:SUPPLEMENT NATURAL VENTIALTION AS NEEDED
Eye Protection:DESIRABLE.
Supplemental Safety and Health
ADD HAZ ING: PIGMENTS 0.4-8%, CELLULOSE NITRATE, ALCOHOLTALKYD, DIOCTYL PHTHALATE 16%,BUTANOL 3%, METHYLENE CHLORIDE 10%, METHYL ETHYL KETONE 5%.PERCENTAGES OF INGREDIENTS ARE APPROXIMATE.-

Chemical Properties

HCC:V3
Vapor Density:>1
Spec Gravity:Evaporation Rate & Reference:BUTYL ACETATE >1
Solubility in Water:SLIGHT
Percent Volatiles by Volume:80

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:BURNING SPRAY MAY PRODUCE TOXIC AND IRRITATING COMPOUNDS

Disposal

Waste Disposal Methods:AVOID INCINERATION OF CAN OR USE ONLY A STRONG CLOSED INCINERATOR.DRIED ENAMEL DISCARD AS NON-DANGEROUS TRASH TO BE BURIED OR BURNED IN ACCORDANCE WITH STATE, FEDERAL AND LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.