

## **KRYLON INERIOR/EXTER ENAMEL AEROSOL 2105**

### **MSDS Number**

BDBBH

### **National Stock Number**

8010-00-132-2864

### **Product Name**

KRYLON INERIOR/EXTER ENAMEL AEROSOL 2105

### **Manufacturer**

BORDEN INC KRYLON DEPARTMENT

### **Product Identification**

Product ID:KRYLON INERIOR/EXTER ENAMEL AEROSOL 2105

MSDS Date:01/01/1985

FSC:8010

NIIN:00-132-2864

MSDS Number: BDBBH

### **Responsible Party**

BORDEN INC., KRYLON DEPARTMENT

630 E WASHINGTON

NORRISTOWN , PA 19404

US

Cage: EO688

### **Contractor**

KRYLON PRODUCTS

SOLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

### **Ingredients**

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 25%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 15%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAANT; 9192

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 10%

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 5 - 10%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 3%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

## Hazards

Effects of Overexposure:DIZZY, CONFUSION,WEAKNESS.

## First Aid

First Aid:INHALATION:REMOVE TO FESH AIR. IF SPRAYED IN EYES, WASH W/WATER 15 MINUTES. SEE A DR.

## Fire Fighting

Extinguishing Media:CO,CO2,FOAM, DRY CHEMICAL

Fire Fighting Procedures:WATER FOG TO COOL CANS TO PREVENT EXPOSURE TO HIGH TEMPS

Unusual Fire/Explosion Hazard:FLAME FRONT IF SPRAYED DIRECTLY AT A OPEN FLAME. CANS MAY BURST WITH VIOLENCE WHEN EXPOSED TO HEAT.

## Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION SOAK UP WITH ABSORBENT MATERIAL. VENTILATE AREA.

## Handling

Handling and Storage Precautions:DO NOT STORE AT TEMPS OVER 120F. AVOID RADIATORS, STOVES, DIRECT SUNLIGHT OR OTHER HEAT SOURCE. HIGH TEMP MAY CAUSE BURSTING.

Other Precautions:AVOID PUNCTURING IF SPRAY IS BURNED DO NOT BREATH IRRITATING OR TOXIC FUMES.

## Exposure Controls

Respiratory Protection:NOT REQUIRED WITH ADEQUAT VENTILATION  
Ventilation:SUPPLEMENT NATURAL VENTIALTION AS NEEDED  
Eye Protection:DESIRABLE.  
Supplemental Safety and Health  
ADD HAZ ING: PIGMENTS 0.4-8%, CELLULOSE NITRATE, ALCOHOLTALKYD, DIOCTYL  
PHTHALATE 16%,BUTANOL 3%, METHYLENE CHLORIDE 10%, METHYL ETHYL  
KETONE 5%.PERCENTAGES OF INGREDIENTS ARE APPROXIMATE.-

## Chemical Properties

HCC:V3  
Vapor Density:>1  
Spec Gravity:Evaporation Rate & Reference:BUTYL ACETATE >1  
Solubility in Water:SLIGHT  
Percent Volatiles by Volume:80

## Stability

Stability Indicator/Materials to Avoid:YES  
Hazardous Decomposition Products:BURNING SPRAY MAY PRODUCE TOXIC AND  
IRRITATING COMPOUNDS

## Disposal

Waste Disposal Methods:AVOID INCINERATION OF CAN OR USE ONLY A STRONG  
CLOSED INCINERATOR.DRIED ENAMEL DISCARD AS NON-DANGEROUS TRASH TO  
BE BURIED OR BURNED IN ACCORDANCE WITH STATE, FEDERAL AND LOCAL  
REGS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.