

KRYLON INTERIOR/EXTER ENAMEL AEROSOL 1501

MSDS Number

BDBBK

National Stock Number

8010-00-132-2865

Product Name

KRYLON INTERIOR/EXTER ENAMEL AEROSOL 1501

Manufacturer

BORDEN INC KRYLON DEPARTMENT

Product Identification

Product ID:KRYLON INTERIOR/EXTER ENAMEL AEROSOL 1501

MSDS Date:01/01/1985

FSC:8010

NIIN:00-132-2865

MSDS Number: BDBBK

Responsible Party

BORDEN INC.,KRYLON DEPARTMENT

630 E WASHINGTON

NORRISTOWN , PA 19404

US

Cage: KO164

Contractor

KRYLON PRODUCTS

SOLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

Ingredients

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 25%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 15%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 10%

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 5 - 10%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 3%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

Hazards

Effects of Overexposure:DIZZY,CONFUSION,WEAKNESS.

First Aid

First Aid:INHALATION:REMOVE TO FRESH AIR.IF SPRAYED IN EYES,WASH WITH WATER 15 MINUTES,SEE A PHYSICIAN.

Fire Fighting

Extinguishing Media:CO,CO2,FOAM,DRY CHEMICAL

Fire Fighting Procedures:WATER FOG TO COOL CANS TO PREVENT EXPOSURE TO HIGH TEMPS

Unusual Fire/Explosion Hazard:FLAME FRONT IF SPRAYED DIRECTLY AT A OPEN FLAME. CANS MAY BURST WITH VIOLENCE WHEN EXPOSED TO HEAT

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION SOAK UP WITH ABSORBENT MATERIAL.VENTILATE AREA.

Handling

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURE OVER 120F.AVOID RADIATORS,STOVES,DIRECT SUNLIGHT OR OTHER HEAT SOURCE.HIGH TEMP MAY CAUSE BURSTING.

Other Precautions:AVOID PUNCTURING IF SPRAY IS BURNED DO NOT BREATHE IRRITATING OR TOXIC FUMES.

Exposure Controls

Respiratory Protection:NOT REQUIRED WITH ADEQUAT VENTILATION
Ventilation:SUPPLEMENT NATURAL VENTILATION AS NEEDED
Eye Protection:DESIRABLE
Supplemental Safety and Health
ADD HAZ ING:PIGMENTS 0.4-8%,CELLULOSE NITRATE,ALCOHOL-ALKYD,DIOCTYL
PHTHALATE 16%,BUTANOL 3%,METHYLENE CHLORIDE 10%,METHYL ETHYL KETONE
5%.PERCENTAGES OF INGREDIENTS ARE APPROXIMATE

Chemical Properties

HCC:V3
Vapor Density:>1
Spec Gravity:Evaporation Rate & Reference:BUTYL ACETATE >1
Solubility in Water:SLIGHT
Percent Volatiles by Volume:80

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:BURNING SPRAY MAY PRODUCE TOXIC AND
IRRITATING COMPOUNDS

Disposal

Waste Disposal Methods:AVOID INCINERATION OF CAN OR USE ONLY A STRONG
CLOSED INCINERATOR.DRIED ENAMEL DISCARD AS NON-DANGEROUS TRASH TO
BE BURIED OR BURNED IN ACCORDANCE WITH STATE,FEDERAL AND LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.