

VV-D-1078 B :DAMPING FLUID

MSDS Number

BDBHK

National Stock Number

9150-00-137-6343

Product Name

VV-D-1078 B :DAMPING FLUID

Manufacturer

NON FLUID OIL CORP

Product Identification

Product ID:VV-D-1078 B :DAMPING FLUID

MSDS Date:01/01/1987

FSC:9150

NIIN:00-137-6343

MSDS Number: BDBHK

Responsible Party

NON-FLUID OIL CORPORATION

Emergency Phone: 201-344-3451

Cage: KO047

Contractor

NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

NEWARK, NJ 07105-3009

US

201-344-3451/800-424-9300(CHEMTREC)

Cage: 76736

Ingredients

SILICONE- DIMETHYLPOLYSILOXANE (MFR SUGGESTED TLV =5MG/CUM

Fraction By Weight: 100%

Hazards

Effects of Overexposure:MILD IRRITATION OF SKIN AND MUCOUS
MEMBRANES.DEFATING OF SKIN IS POSSIBLE;EYES;TEMPORARY DISCOMFORT.

First Aid

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

Fire Fighting

Flash Point:>250F/121C (COC)

Extinguishing Media:CO*2,DRY CHEMICAL,FOAM & FOG-WATER

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.

Unusual Fire/Explosion Hazard:NONE NOTED

Accidental Release

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;STOP
FLOW.ELIMINATE IGNITION SOURCES;RECOVER FREE PRODUCTS;ADD INERT
ABSORBENT MATERIALS AND RECOVER FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:STORE IN COOL DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT,OPEN FLAMES&OXIDIZING MATERIALS.

Other Precautions:DO NOT BREATHE VAPORS;AVOID CONTACT WITH EYES & SKIN;WASH THOROUGHLY AFTER EACH USE.

Exposure Controls

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Supplemental Safety and Health

MSDS DATED:MAY,1987

Chemical Properties

HCC:V6

Boiling Pt:B.P. Text:>500F/260C

Vapor Pres:Spec Gravity:0.915

Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR,COLORLESS LIQUID,NO ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:EXTREME HEAT,OPEN FLAMES.

Hazardous Decomposition Products:OXIDES OF CARBON MAY FORM ON INCOMPLETE COMBUSTION

Disposal

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.