

BOSTIK

MSDS Number

BDBHW

National Stock Number

8010-00-138-1760

Product Name

BOSTIK

Manufacturer

BOSTIK FINCH INC

Product Identification

Product ID: BOSTIK
MSDS Date: 01/01/1985
FSC: 8010
NIIN: 00-138-1760
Kit Part: Y
MSDS Number: BDBHW

Responsible Party

BOSTIK-FINCH, INC.
434 W. MEAT ST.
ORANGE , CA 92661
US
Cage: KO195

Contractor

BOSTIK-FINCH, INC.
ORANGE, CA 92661
US
714-637-1750; CHEMTREC 800-424-9300
Cage: KO195

Ingredients

SOLVENTS
Fraction By Weight: 45.0%
ACGIH TLV: 00-400 PPM

POLYESTER RESIN
Fraction By Weight: 19.1%

ISOCYANADTE PREPOLYMER(ALIPHATIC)
Fraction By Weight: 16.5%

PIGMENTS
Fraction By Weight: 19.2%

ADDITIVES

Fraction By Weight: 0.2%

Hazards

Effects of Overexposure:INHALE-IRRITATION NOSE & THROAT. MAY CAUSE NAUSEA OR VOMITING. MAY CAUSE EYE & SKIN IRRITATION.

First Aid

First Aid:SKIN-WASH WITH SOAP & WATER. EYE-FLUSH WITH WATER; CONSULT DOCTOR. INHALE-REMOVE TO FRESH AIR;CONSULT DOCTOR. INGESTION. INDUCE VOMITING; CONSULT DOCTOR.

Fire Fighting

Flash Point:23F, -5C TCC

Lower Limits:1.1

Extinguishing Media:CO2 O DRY CHEM FOR SMALL; ALCOHOL FOAM FOR LARGE FIRES.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. USE AIR SUPPLIED RESCUE EQUIPMENT.

Unusual Fire/Explosion Hazard:DO NOT APPLY TO HEATED SURFACES OR IN AREAS WHERE ELECTTRICAL SPARKS MAY BE PRESENT.

Accidental Release

Spill Release Procedures:ABSORB WITH SAWDUST OR OIL ABSORBING COMPOUND. WASH AREA WITH DETERGENT AND WATER. USE ADEQUATE VENTILATION TO CLEAR FUMES FROM AREA. AVOID SPARKS.

Handling

Handling and Storage Precautions:STORE UNDER 100F. KEEP AWAY HEAT, SPARKS & OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

Exposure Controls

Respiratory Protection:AIR SUPPLIED RESPIRATOR OR SUITABLE CHEMICAL CARTRIDGE.

Ventilation:TO MEET TLV

Protective Gloves:SOLVEN RESISTAN

Eye Protection:GOGGLES OR FACE SHIELD.

Other Protective Equipment:COVERALLS, APRON, NON-SPARKING SAFETY SHOES, ETC.

Supplemental Safety and Health

Chemical Properties

HCC:F2

Boiling Pt:B.P. Text:175-320F

Vapor Density:>AIR

Evaporation Rate & Reference:Percent Volatiles by Volume:57.4

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS

Hazardous Decomposition Products:CO & COMBUSTION PRODUCTS OF VARIOUS PIGMENTS

Disposal

Waste Disposal Methods:INCINERATE WITH CARE SANITARY LAND FILL PREFERBLE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

