

AP 218 A

MSDS Number

BDBKX

National Stock Number

8040-00-139-3677

Product Name

AP 218 A

Manufacturer

ARROWHEAD PRODUCTS

Product Identification

Product ID:AP 218 A MSDS Date: 01/01/1985 FSC:8040 NIIN:00-139-3677 MSDS Number: BDBKX

Responsible Party

ARROWHEAD PRODUCTS

Emergency Phone: (714)828-7770

Cage: KO202

Contractor

VESPER CORP ARROWHEAD PRODUCTS DIVISION

LOS ALAMITOS, CA 90720-3514

Cage: 70628

US

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 60.0% OSHA PEL200 PPM/150 STEL ACGIH TLV: 50 PPM; 9293 EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ORGANIC POLYMERS

Fraction By Weight: UNKN

FILLERS UNSPECIFIED

Fraction By Weight: UNKN ACGIH TLV: NOT SPECIFIED

Hazards

Effects of Overexposure: HEADACHE, DIZZINESS, SLIGHTLY IRRITATING TO

EYES AND SKIN.



First Aid

First Aid:SKIN: WASH WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY. EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. VAPORS: REMOVE TO FRESH AIR; IF UNCONSCIOUS, USE ARTIFICAL RESPIRATION.

Fire Fighting

Flash Point: 41F, T.C.C.

Extinguishing Media:FOAM, CO2, STEAM, WATERFOD, OR DRY CHEMICAL

Fire Fighting Procedures: DO NOT USE WATER.

Unusual Fire/Explosion Hazard: VAPOR FORMS EXPLOSIVE MIXTURE WITH AIR

BETWEEN UPPER AND LOWER EXPLOSIVE LIMITS.

Accidental Release

Spill Release Procedures: AVOID OPEN FLAME OR SPARK SOURCES. PROVIDE ADEQUATE VENTILATION.

Handling

Handling and Storage Precautions: AVOID OPEN FLAMES AND SPARK SOURCES. AVOID SPLASH-FILLING. PROVIDE ADEQUATE VENTILATION. AVOIDXCESSIVE HEAT.

Exposure Controls

Ventilation: MECHANICAL AND/OR LOCAL EXHAUST TO KEEP EXPOSURE < TLV

Protective Gloves: POLYVINYL ALCOH

Eye Protection: CHEMICAL SAFETY GOGGLES

Other Protective Equipment: APRON

Supplemental Safety and Health

MSDS UPDATED ADDRESS:4411 KATELLA AVE, LOS ALAMITOS, CA 90720.ITEM IS TWO PARTS KIT.THIS IS AP218A,CONTAINING SAME SOLVENT AS THAT OF AP 218 B.KEY1:F3.

Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:230-231F

Vapor Density: 3.8

Appearance and Odor: TOLUENE ODOR, PINK OR GRAY

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CO, CO2 WHEN COMBUSTED

Disposal

Waste Disposal Methods: CONTROLLED INCINERATION OR BURIAL IN APPROVED LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.