

DRO55-CONCENTRATE

MSDS Number

BDBNS

National Stock Number

8010-00-141-2952

Product Name

DRO55-CONCENTRATE

Manufacturer

DEVOE AND RAYNOLDS CO INC

Product Identification

Product ID:DRO55-CONCENTRATE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-141-2952

MSDS Number: BDBNS

Responsible Party

DEVOE & RAYNOLDS CO INC

Emergency Phone: 714-686-6930

Cage: EO559

Contractor

DEVOE COATINGS CO DIV OF GROW GROUP INC

RIVERSIDE, CA 92507-2606

US

Cage: 70506

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 86.0%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 12.0%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight:

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2-BUTOXYETHANOL

CAS: 111-76-2

RTECS: KJ8575000

Fraction By Weight:

OSHA PELS, 50 PPM

ACGIH TLV: S, 25 PPM; 9293

Hazards

Effects of Overexposure: INHALATION-HEADACHE, NAUSEA, DIZZINESS.
PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION.

First Aid

First Aid: INHALATION-MOVE TO FRESH AIR. SKIN CONTACT-FLUSH WITH LARGE AMOUNT OF WATER; REMOVE CONTAMINATED CLOTHING. EYE CONTACT-FLUSH WITH CLEAN WATER FOR AT LEAST 15 MIN.-CALL PHYSICIAN.

Fire Fighting

Flash Point: 43 F, 6.1 C PMCC

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN BY FIREMEN

Unusual Fire/Explosion Hazard: USE WATER TO COOL CONTAINERS EXPOSED TO FIRE

Accidental Release

Spill Release Procedures: AVOID BREATHING VAPORS; EXTINGUISH IGNITION SOURCES IN AREA. AVOID CONTACT WITH LIQUID.

Handling

Handling and Storage Precautions: DO NOT STORE AT ELEVATED TEMPERATURES.

Other Precautions: CLOSE CONTAINERS AFTER USE

Exposure Controls

Respiratory Protection: IN CONFINED AREA USE U.S. BUR. OF MINES APPROVED RESPIRATOR.

Ventilation: LOCAL-SUFFICIENT TO KEEP CONCENTRATION BELOW GIVEN TLV.

Protective Gloves: PROLONGED USE

Eye Protection: SOLVENT RESISTANT

Other Protective Equipment: NORMAL PROTECTIVE CLOTHING

Supplemental Safety and Health

BOILING POINT: 80-172.8 C

Chemical Properties

HCC: V3

Boiling Pt: B.P. Text: 176-343 F

Vapor Density: >1

Spec Gravity: 0.95

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water:SLIGHT
 Appearance and Odor:MOBILE LIQUID WITH VOLATILE SOLVENTS. RED COLOR
 Percent Volatiles by Volume:75.7

Stability

Stability Indicator/Materials to Avoid:YES
 OXIDIZING MATERIALS SOFTEN RUBBER
 Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

Disposal

Waste Disposal Methods:DISPOSE OF IN CLOSED CONTAINERS AWAY FROM
 IGNITION SOURCES.

Disclaimer (provided with this information by the compiling agencies):
 This information is formulated for use by elements of the Department
 of Defense. The United States of America in no manner whatsoever,
 expressly or implied, warrants this information to be accurate and
 disclaims all liability for its use. Any person utilizing this
 document should seek competent professional advice to verify and
 assume responsibility for the suitability of this information to their
 particular situation.