

# **U-20 AGGREGATES**

## **MSDS Number**

**BDBQP** 

#### **National Stock Number**

5610-00-141-7958

### **Product Name**

U-20 AGGREGATES

### Manufacturer

WESTPAC PRODUCTS CO INC

## **Product Identification**

Product ID:U-20 AGGREGATES MSDS Date:01/01/1987 FSC:5610 NIIN:00-141-7958 Kit Part:Y MSDS Number: BDBQP

# **Responsible Party**

WESTPAC PRODUCTS CO INC

Emergency Phone: 415-632-3778

Cage: 4Z694

Contractor

WESTPAC PRODUCTS CO INC OAKLAND, CA 94621-1326

US

Cage: 4Z694

Ingredients

SILICA, CRYSTALLINE - QUARTZ

CAS: 14808-60-7 RTECS: VV7330000 OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

#### **Hazards**

Effects of Overexposure: PULMONARY FIBROSIS & SILICOSIS FROM LONG TERM EXPOS TO RESPIRABLE DUST.

#### First Aid

First Aid:EYES:WASH WITH WATER.SKIN:WASH W/ SOAP & WATER.

# **Fire Fighting**

Flash Point:NONFLAM SOLID Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE Fire Fighting Procedures:USE SCBA & EYE PROTECTION IN HEAVY CONCENTRATIONS OF DUST Unusual Fire/Explosion Hazard:NONE PER MFR.

# **Accidental Release**

Spill Release Procedures: SWEEP OR VACUUM FOR RECOVERY OR DISPOSAL TO PREVENT GENERATION OF DUST.



## Handling

Handling and Storage Precautions: REDUCE AIRBORN DUST THROUGH GOOD HOUSEKEEPING PRACTICES.USE APPR RESP, HAND, & EYE PROTECTION. MAINTAIN DUST CONC Other Precautions: INCREASED HEALTH RISK FROM SMOKING & EXPOS TO SILICA DUST.WORKERS W/ PULMONARY DISEASE SHOULD AVOID EXPOS TO SILICA DUST.

# **Exposure Controls**

Respiratory Protection: NIOSH/MSHA APPR PARTICULATE RESP, IF TLV

EXCEEDED.SEE SPP DATA

Ventilation: LOC EXHST OR MECHANICAL TO MEET TLV REQUIREMENTS

Protective Gloves: LEATHER

Eye Protection: SFTY GLASSES W/ SIDE SHLD

Other Protective Equipment: HEARING PROTECTORS DURING ABRASIVE BLASTING

OPERATIONS.

Supplemental Safety and Health

MSDS PREP:87041.SPEC DATA:TYPE 1.PART C OF A 3-PART KIT.RESP

PROTECTION; AIR SUPPLIED HOODS FOR BLASTERS. CONDITIONS TO AVOID: TEMP

>1598F,870C.KEY1:N1.

# **Chemical Properties**

HCC:N1

Boiling Pt:B.P. Text:2230F,1221C

Spec Gravity: 2.60

Evaporation Rate & Reference: N/R(PER MFR)

Solubility in Water: NONE

Appearance and Odor: GRANULAR, LIGHT BROWNISH COLOR, ODORLESS

## **Stability**

Stability Indicator/Materials to Avoid:YES STRONG ALKALIS, HYDROFLUORIC ACID Hazardous Decomposition Products: NONE PER MFR

## **Disposal**

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/ FEDERAL, STATE, & LOCAL REGULATIONS.AS AN INERT SOLID WASTE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.