

02-Y-24 CTLST,YELLOW,EPOXY POLYAMIDE PRIMER

MSDS Number

BDBSZ

National Stock Number

8010-00-142-9279

Product Name

02-Y-24 CTLST,YELLOW,EPOXY POLYAMIDE PRIMER

Manufacturer

DEFT CHEMICAL COATINGS

Product Identification

Product ID:02-Y-24 CTLST,YELLOW,EPOXY POLYAMIDE PRIMER

MSDS Date:01/01/1985

FSC:8010

NIIN:00-142-9279

Kit Part:Y

MSDS Number: BDBSZ

Responsible Party

DEFT CHEMICAL COATINGS

17451 VON KARMAN AVE

IRVINE , CA 92714-6205

US

Emergency Phone: NONE

Cage: EO418

Contractor

DEFT, INC.

IRVINE, CA 92614

US

949-474-0400

Cage: 33461

Ingredients

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 20.0%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure:EYES:MODERATE IRRIT;SKIN:POSSIBLE IRRIT BY
SOLVENTS;INH:SOLVENT VAPORS CAN CAUSE IRRIT OR NARCOSIS

First Aid

First Aid:SKIN:WIPE OFF WITH A RAG THEN THOROUGH RINSING W/H*20 &
WASHING W/MILD SOAP AND WATER;EYES:FLUSH W/WATER FOR AT LEAST 10

MIN & CONSULT AN EYE PHYSICIAN;INH:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED.

Fire Fighting

Flash Point:20F(-6.6C)-TOC
Lower Limits:1.7
Extinguishing Media:CO*2,DRY CHEM,FOAM
Fire Fighting Procedures:DO NOT USE H*2O STREAM ON FIRE.H*2O SPRAY/FOG IS MORE EFFECTIVE
Unusual Fire/Explosion Hazard:CAUTION AGAINST APPLICATION TO HOT SURFACES & USE IN AREAS WHERE SOURCES OF IGNITION MAY BE PRESENT.

Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN SOURCES.USE SAFETY EQUIP.VENTILATE AREA.STOP LEAK W/O RISK.ABSORB SMALL SPILL W/OIL ABSORBING COMPD/RAGS;DIKE LG SPILL.PUMP LIQ TO SALVAGE TANK.SHOVEL UP RESIDUE INTO COVERED DRUMS;PER MFR,FLUSH AREA W/LG AMOUNT OF WATER.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTILATED,LOW FIRE RISK AREA.KEEP CONTAINERS TIGHTLY CLOSED.KEEP AWAY FROM HEAT,SPARK OR OPEN FLAME.
Other Precautions:AVOID PROLONGED INHALATION OF VAPOR.PER MFR,WATER SPRAY OR FOG CAN BE USED EFFECTIVELY ON FIRE AND TO COOL HEAT/FIRE EXPOSED CONTAINERS.

Exposure Controls

Respiratory Protection:GOOD VENTILATION IS NEEDED HOWEVER USE NIOSH APPROVED SCBA FOR PAINTS.
Ventilation:USE ADEQUATE VENTILATION USING EXHAUST FAN.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES.
Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED OR REPEATED CONTACT.
Supplemental Safety and Health
TWO PART KIT. THIS IS CATALYST. SEE P/N IND "A" FOR BASE; ALSO SEE P/N IND "B" FOR OTHER HAZARD INGREDIENTS; MIL SPEC REFERENCE: MIL-P-23377D, TYPE 1. KEY1:J1.

Chemical Properties

HCC:F2
Boiling Pt:Boiling Point:175-331F
Vapor Density:>1.0
Specific Gravity:0.8484
Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR THIN LIQUID,ODOR OF MEK
Percent Volatiles by Volume:82.3

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZING & CORROSIVE MATERIALS.
Stability Condition to Avoid:SOURCE OF IGNITION,SPARK,HEAT & OPEN FLAME

Disposal

Waste Disposal Methods:KEEP IN CLOSED CONTAINERS PENDING DISPOSAL.MFR SUGGESTED,DISPOSE IN TIGHTLY CLOSED CONTAINERS & FINALLY DISPOSE BY SANITARY LANDFILL IN ACCORDANCE WITH APPLICABLE REGS;HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL FEDERAL,STATE,& LOCAL REGULATIONS CONCERNING WASTE DISPOSAL

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.