

GT ALUMINUM LACQUER

MSDS Number

BDCDL

National Stock Number

8010-00-145-0166

Product Name

GT ALUMINUM LACQUER

Manufacturer

SEYMOUR OF SYCAMORE INC

Product Identification

Product ID:GT ALUMINUM LACQUER

MSDS Date:01/01/1985

FSC:8010

NIIN:00-145-0166

MSDS Number: BDCDL

Responsible Party

SEYMOUR OF SYCAMORE, INC.

Emergency Phone: 815/895-9101

Cage: 59581

Contractor

SEYMOUR OF SYCAMORE

SYCAMORE, IL 60178-1343

US

815-895-9101/800-255-3924

Cage: 59581

Ingredients

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

DIISOBUTYL KETONE

CAS: 108-83-8

RTECS: MJ5775000

OSHA PEL50 PPM

ACGIH TLV: 25 PPM; 9293

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 48%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:INHALATION: ANESTHETIC, IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE, RESTORE BREATHING. NOTIFY PHYSICIAN. EYES: FLUSH WITH COPIOUS QUANTITIES OF RUNNING WATER FOR AT LEAST 15 MINUTES. SKIN:REMOVE WITH SOAP AND WATER, REMOVE CONTAMINATED CLO THING. TAKE TO PHYSICIAN FOR EYE CONTACT.

Fire Fighting

Flash Point:-10F

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM.

Fire Fighting Procedures:WEAR GOGGLES AND SELF CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CAN.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS, VENTILATE AREA.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING.

Exposure Controls

Respiratory Protection:AVOID CONTINUOUS BREATHING OF VAPORS AND SPRAY MIST

Ventilation:USE WITH ADEQUATE VENTILATION

Supplemental Safety and Health

ALSO CONTAINS ETHYL ALCOHOL-1000PPM, ETHYL ACETATE-400PPM, 6.4%

ACETONE-750PPM, 25% PROPELLANT:50-50 BLEND PROPANE/ISOBUTA.

Chemical Properties

HCC:F2

Boiling Pt:B.P. Text:NA

Vapor Density:>AIR

Evaporation Rate & Reference:FASTER THAN ETHER

Percent Volatiles by Volume:85

Stability

Stability Indicator/Materials to Avoid:YES

NA

Hazardous Decomposition Products:FUMES MAY CONTAIN CARBON MONOXIDE,
OXIDES-NITROGEN,PHOSGENE

Disposal

Waste Disposal Methods:DO NOT INCINERATE AEROSOL, DISPOSE OF IN
ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.