

PETROFLUID 822

MSDS Number

BDCPQ

National Stock Number

9150-00-149-7432

Product Name

PETROFLUID 822

Manufacturer

PENRECO DIV OF PENNZOIL CO

Product Identification

Product ID:PETROFLUID 822

MSDS Date:01/01/1985

FSC:9150

NIIN:00-149-7432

MSDS Number: BDCPQ

Responsible Party

PENRECO DIVISION OF PENNZOIL CO

700 MILIAM ST PENNZOIL PL

HOUSTON , TX 77252

US

Emergency Phone: 800-245-3952

Info Phone: 800-245-3952

Cage: JO941

Contractor

PENRECO, DIV OF PENNZOIL CO

2967

HOUSTON, TX 77252

US

800-245-3952

Cage: 86459

Ingredients

SYNTHETIC OIL

DIBASIC ACID ESTER

Hazards

Effects of Overexposure:EYE: IRRIT. SKIN: IRRIT. INGEST: LOCAL IRRIT OF
MUC MEMB OF THOAT, MOUTH, ESOPHAGUS, STOMACH.

First Aid

First Aid:EYE: WASH IMMEDIATELY WITH WATER FOR 15 MIN. CALL PHYSICIAN. SKIN:WASH
WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING & WASH BEFORE REUSE.
INGEST: DO NOT INDUCE VOMITING (ASPIRATION HAZARD)

Fire Fighting

Flash Point Method:COC

Flash Point:424F,218C

Extinguishing Media:CO*2,DRY CHEM, FOAM
Fire Fighting Procedures:WATER MAY BE USED TO COOL HEAT-EXPOSED CANS.
Unusual Fire/Explosion Hazard:PROD OF COMBUSTION:CO,CO*2,SMOKE.
MATERIAL MUST BE HEATED ABOVE FLASH POINT TO BE A FIRE HAZARD.

Accidental Release

Spill Release Procedures:SPREAD OIL DRY MATERIAL ON SPILL & SWEEP UP OR
DILUTE SPILL W/PETROLEUM SOLVENT & WIPE UP. PROVIDE ADEQUATE VENT &
AVOID SOURCES OF IGNITION. STORE IN COVERED MARKED METALLIC
CONTAINERS AND DISPOSE OF AS SOON AS POSSIBLE.

Handling

Handling and Storage Precautions:STORE IN COVERED MARKED METALLIC
CONTAINERS. STORE IN COOL WELL VENTED AREA. CONTROL IGNITION
SOURCES. GROUND CANS PRIOR TO PUMPING OR TRANSFERRING.
Other Precautions:FIRE EXTINGUISHERS MUST BE KEPT READILY AVAILABLE &
ALL PERSONNEL TRAINED PROPERLY. DO NOT MIX W/STRONG OXIDANTS. DO
NOT TRANSFER TO UNMARKED CONTAINERS. AUTOIGNITION TEMP: 630F;332C.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR FOR PARTICULAR
EXPOS OF CONCERN.(MFR)
Ventilation:TO KEEP CONCENTRATION BELOW TLV. USE EXPLOSION-PROOF EQUIP.
Protective Gloves:POLYETHYLENE
Eye Protection:SFTY GOG W/FACE SHIELD
Other Protective Equipment:IMPERVIOUS POLYETHYLENE BOOTS/APRON ETC.
Supplemental Safety and Health
TLV=5 MG/CUM FOR MIST & 500 PPM FOR VAPORS GENERATED UPON HEATING.
CONTAINER: 1 GALLON.

Chemical Properties

HCC:V6
Vapor Pres:Vapor Density:>1
Spec Gravity:0.85
Evaporation Rate & Reference:Solubility in Water:NEGLIBLE
Appearance and Odor:RED TRANSPARENT FLUID.
Percent Volatiles by Volume:0

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS

Disposal

Waste Disposal Methods:MFR RECOMMENDS INCINERATION. DISPOSAL METHOD
MUST BE IAW FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.