

PAINT REMOVER

MSDS Number

BDDHJ

National Stock Number

8010-00-160-5798

Product Name

PAINT REMOVER

Manufacturer

CHEMICAL COMMODITIES AGENCY INC

Product Identification

Product ID:PAINT REMOVER

MSDS Date:01/01/1987

FSC:8010

NIIN:00-160-5798

MSDS Number: BDDHJ

Responsible Party

CHEMICAL COMMODITIES AGENCY, INC.

27447 PACIFIC STREET

HIGHLAND , CA 92346-2640

US

Emergency Phone: 909-864-2310

Info Phone: 909-864-2310/FAX 6220 D. ANGELO

Cage: 60777

Contractor

CHEMICAL COMMODITIES AGENCY, INC.

HIGHLAND, CA 92346-2640

US

909-864-2310

Cage: 60777

Ingredients

PARAFFINS (INCLUDING NAPHTHENES) AROMATICS

BENZENE (SARA III)

CAS: 71-43-2

RTECS: CY1400000

OSHA PEL1PPM/5STEL;1910.1028

ACGIH TLV: 10 PPM; A2; 9192

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

Hazards

Effects of Overexposure:MAY CAUS SKIN IRRIT UPON PRLNG USE/REPEAT
CONTCT.INGEST CAN RESULT IN ASPIRAT OF LGHT HYDROCARBN(SUP

First Aid

First Aid: IF SWALLOW, DO NOT INDUCE VOMITING. CALL DR. WASH EYES WITH FRESH WATER FOR 15 MIN. IF IRRITATION CONTINUES, SEE DR. WASH THOROUGHLY WITH SOAP & WATER AFTER SKIN CONTACT. LAUNDRY CONTAMINATES CLOTHING. IF INHALED, REMOVE TO FRESH AIR. IF BREATHING STOPPED, APPLY ARTIFICIAL RESPIRATION. CALL DR.

Fire Fighting

Flash Point: 105°F TCC 41°C
Extinguishing Media: CO₂, DRY CHEM, FOAM, WATER SPRAY
Fire Fighting Procedures: DO NOT ENTER CONFINED AREA WITHOUT PROPER EQUIPMENT. USE SELF-CONTAINED SUPPLY
Unusual Fire/Explosion Hazard: DO NOT STORE NEAR FIRE, HEAT OR OPEN FLAMES.

Accidental Release

Spill Release Procedures: ABSORB SPILLS WITH ABSORBENT CLAY, DIATOMACEOUS EARTH. A FIRE OR VAPOR HAZARD MAY EXIST SINCE THESE MATERIALS WILL ONLY ABSORB LIQUID, NOT VAPOR

Handling

Handling and Storage Precautions: KEEP AWAY FROM PILOT LIGHTS, WELDING EQUIPMENT, ELECTRICAL SWITCHES. FIRE HAZARD IS GREATER AS LIQUID TEMPERATURE RISES ABOVE 85°F.
Other Precautions: HARMFUL OR FATAL IF SWALLOWED, KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection: WHERE APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR UNLESS VENTILATION IS ADEQUATE.
Ventilation: MECHANICAL-RECOMMENDED
Protective Gloves: RUBBER
Eye Protection: SAFETY GOGGLES
Other Protective Equipment: IMPERVIOUS PROTECTIVE CLOTHING.
Supplemental Safety and Health
SPECIFIC FIRE FIGHTING PROCEDURE: BREATHING APPARATUS. EFFECTS OF OVEREXPOSURE: LIQUID WHICH CAN CAUSE PNEUMONITIS.

Chemical Properties

HCC: F4
Boiling Point: B.P. Text: 314-387°F
Vapor Pressure: 5MM
Vapor Density: 4.9
Specific Gravity: .79
Evaporation Rate & Reference: BU AC 0.13
Solubility in Water: INSOLUBLE
Appearance and Odor: COLORLESS LIQUID
Percent Volatiles by Volume: 99.+

Stability

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING MATERIALS
Hazardous Decomposition Products: NORMAL COMBUSTION FORMS CO₂ & WATER VAPOR, INCOMPLETE COMBUSTION-CO

Disposal

Waste Disposal Methods: PLACE CONTAMINATED MATERIAL IN DISPOSABLE CONTAINERS & BURY IN APPROVED DUMPING AREA.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.