

793716 LAC SPRAYING WHITE 17875

MSDS Number

BDDMR

National Stock Number

8010-00-161-7337

Product Name

793716 LAC SPRAYING WHITE 17875

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:793716 LAC SPRAYING WHITE 17875

MSDS Date:01/01/1985

FSC:8010

NIIN:00-161-7337

MSDS Number: BDDMR

Responsible Party

PRATT AND LAMBERT INC

16116 E 13TH ST

WICHITA , KS 67201

US

Emergency Phone: 716-873-6000 DOT EMER 8002553924

Info Phone: 316-733-1361

Cage: 61196

Contractor

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

ISOBUTYL ACETATE

RTECS: NP9100000

Fraction By Weight: 25%

ACGIH TLV: 150PPM

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight: 8%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 15%

OSHA PEL100 PPM

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 15%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM/300STEL;9394

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure:INHAL:ANEST,IRRIT OF RESPIR TRACT OR ACUT NERV
SYS DEPRESN,HDACH,DIZZ,CONFUS,UNCONSCIOUS,COMA.

First Aid

First Aid:IN CASE OF CONTACT,FLUSH SKIN & EYES W/PLENTY OF WATER WHILE
REMOVING CONTAMINATED CLOTHING.IF INHALED,REMOV TO FRESH AIR.CALL A
PHYSICIAN IF SUMPTOMS PERSIST.

Fire Fighting

Flash Point:21.F TCC -6C

Lower Limits:.90

Extinguishing Media:USE FIRE EXTING(CO*2,DRY CHEM OR ALCOH FOAM)LO
FIRE-POLYMER

Fire Fighting Procedures:SELF-CONTAINED BREATH APPARATUS SHLD BE AVAIL
F/FIREMEN.

Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTLY CLOS:ISOLAT FR
HEAT,ELECTR EQPMT.SPARKS & OPEN FLAM.CLOS CONTNRS MAY EXPLO(SUP

Accidental Release

Spill Release Procedures:REMOV ALL SOURCES OF IGNITION(FLAMES,HOT
SURFACES,& ELECTRICAL,STATIC OR FRICTIONAL SPARKS)AVOID BREATHING
VAPORS.VENTILATE AREA.REMOVE W/INERT ABSORBENT & NON-SPARKING
TOOLS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG
QUANTITIES IN BLDG DESIGNED TO COMPLY W/OSHA 1910.106.
Other Precautions:CONTNRS GROUNDED WHEN POURING.AVD FRE FAL OF LIQD.IN
EXCES OF FEW INCHS.DON'T FLAM CUT,BRAZ OR WELD COATED MATRL W/OBUR
OF MNES APPRVD RESPIR OR APPROP VENT.AD LABL WARN"DONOT TAK
INTERNALY

Exposure Controls

Respiratory Protection:OUTDOOR/OPEN AREAS,USE BUR. OF MINES APPRVD MECH
FILTR RESPIRATOR.
Ventilation:PROVID GEN DILUT OR LOC EXHAUST VENT IN VOL TO KEEP BELOW
TLV
Protective Gloves:F/REPTD CONTACT
Eye Protection:SAFETY EYEWEAR
Other Protective Equipment:PRVNT PROLONG SKIN CONTACT TO CONTAMINATED
CLOTHING.
Supplemental Safety and Health
UNUS FIRE & EXPLOR HAZ:WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY TO VERY
HOT SURFACES.

Chemical Properties

HCC:F2
Boiling Pt:B.P. Text:174-290F
Vapor Density:HEAVY
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:80

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID FIRES,HEAT & HOT SURFACES.

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOC,STATE & FEDERAL
REGULATIONS.INCINERATE IN APPRVD FACILITY. DO NOT INCINERATE CLOSED
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.