

## **793-716**

### **MSDS Number**

BDDMS

### **National Stock Number**

8010-00-161-7337

### **Product Name**

793-716

### **Manufacturer**

PRATT AND LAMBERT INC

### **Product Identification**

Product ID:793-716

MSDS Date:01/01/1985

FSC:8010

NIIN:00-161-7337

MSDS Number: BDDMS

### **Responsible Party**

PRATT AND LAMBERT INC

945 BURLINGTON

KANSAS CITY , MO 64141

US

Emergency Phone: 316-733-1361

Cage: 92216

### **Contractor**

PRATT AND LAMBERT INC

206

KANSAS CITY, MO 64141

US

Cage: 92216

### **Ingredients**

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight: 8.0%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

Fraction By Weight: 25.0%

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192  
EPA Report Quantity: 5000 LBS  
DOT Report Quantity: 5000 LBS

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6  
RTECS: SE7555000  
Fraction By Weight: 15.0%  
OSHA PEL100 PPM

TOLUENE (SARA III)

CAS: 108-88-3  
RTECS: XS5250000  
Fraction By Weight:  
OSHA PEL200 PPM/150 STEL  
ACGIH TLV: 50 PPM; 9293  
EPA Report Quantity: 1000 LBS  
DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0  
RTECS: NT8050000  
Fraction By Weight: < 5%  
OSHA PEL400 PPM/500 STEL  
ACGIH TLV: 400 PPM/500STEL;9192

## Hazards

Effects of Overexposure:INHAL:ANESTHETIC & IRRIT. TO AIRWAY;IRRIT-SKIN  
/EYE; HEADACHE,DIZZY,COMA

## First Aid

First Aid:FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING  
CONTAM. CLOTHING. INHAL: REMOVE TO FRESH AIR. CALL MD. IF SYMPTOMS  
PERSIST

## Fire Fighting

Flash Point:12 F,-6 C, TCC  
Lower Limits:.9  
Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL;POLYMER  
FOAM-LARGE FIRE  
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS ABAILABLE  
FOR FIREMEN  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE DUE TO PRESURE BUILD-UP

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT  
SURFACES, & ELECTRICAL, STATIC, OR FREICTIONAL SPARKS). AVOID  
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND  
NON-SPARKING TOOLS.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE AMTS. IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.  
Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES, DO NOT FLAME CUT,BRAZE, OR WELD COATED MATERIAL WITHOUT VENILATION.

## Exposure Controls

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER FILTER OR HOOD  
Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING  
Protective Gloves:ALOT OF CONTACT  
Eye Protection:USE EYEWEAR IF SPLASHING  
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING  
Supplemental Safety and Health  
BOILING RANGE 79-143C, ALSO CONTAINS METHYL ETHYL KETONE 15% AND CELLOSOLUE ACETARE

## Chemical Properties

HCC:F2  
Boiling Pt:B.P. Text:174-290F  
Evaporation Rate & Reference:< ETHER  
Appearance and Odor:WHITE PAPER  
Percent Volatiles by Volume:80.0

## Stability

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:FIRES, HEAT, & HOT SURFACES

## Disposal

Waste Disposal Methods:DISPOSE IAW LOCAL,STATE AND FED. REGULATIONS. INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.