

## **796034 FEDERAL SPEC COATING,OBLITERATING**

### **MSDS Number**

BDDNG

### **National Stock Number**

8010-00-161-7392

### **Product Name**

796034 FEDERAL SPEC COATING,OBLITERATING

### **Manufacturer**

PRATT AND LAMBERT INC

### **Product Identification**

Product ID:796034 FEDERAL SPEC COATING,OBLITERATING

MSDS Date:01/01/1985

FSC:8010

NIIN:00-161-7392

MSDS Number: BDDNG

### **Responsible Party**

PRATT AND LAMBERT INC

16116 E 13TH ST

WICHITA , KS 67201

US

Emergency Phone: 716-873-6000 DOT EMER 8002553924

Info Phone: 316-733-1361

Cage: 61196

### **Contractor**

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

### **Ingredients**

ISOBUTYL ACETATE

RTECS: NP9100000

Fraction By Weight: 25%

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight: 8%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 8%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

NAPHTHA ALIPHATIC

Fraction By Weight: 8%

ACGIH TLV: 200PPM

## Hazards

Effects of Overexposure:INHAL:ANEST,IRRIT OF REPIR TRACT OR ACUT NERV  
SYS DEPRESN,HDACH,DIZZ,CONFUS,UNCONSCIOUS, COMA.

## First Aid

First Aid:IN CASE OF CONTACT,FLUSH SKIN & EYES W/PLENTY OF WATER WHILE  
REMOVING CONTAMINATED CLOTHING.IF INHALATED,REMOVE TO FRESH AIR.  
CALL A PHYSCIAN IF SYMPTOMS PERSIST.

## Fire Fighting

Flash Point:13F TCC-11C

Lower Limits:.90

Extinguishing Media:USE FIRE EXTING(CO\*2,DRY CHEM OR ALCOH FOAM)LO

FIRE-POLYMER

Fire Fighting Procedures:SELF-CONTAINED BREATH APPARATUS SHLD BE AVAIL  
F/FIREMEN.

Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTLY CLOS:ISOLAT FR  
HEAT,ELECTR EQPMT,SPARKS & OPEN FLAME,CLOS CONTNRS MAY EXPLO(SUP

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT  
SURFACES,& ELECTRICAL, STATIC, OR FRICTIONAL SPARKS)AVOID BREATHING  
VAPORS.VENTILATE AREA.REMOVE W/INERT ABSORBENT & NON-SPARKING  
TOOLS.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F STORE LG  
QUANTITIES IN BLDG DESIGNED TO COMPLY W/OSHA 1910.106.

Other Precautions:CONTNRS GROUNDED WHEN POURING.AVD FRE FALL OF LIQD IN  
EXCES OF FEW INCHES. DON T FLAM CUT,BRAZE OR WELD COATED MATRL W/O  
BUR MNES APPRVD RESPIR OR APPRVD VENT.ADD LABL WARN"DO NOT TAKE  
INTERN.

## Exposure Controls

Respiratory Protection:OUTDOOR/OPEN AREAS,USE BUR.OF MINES APPRVD MECH

FILTR RESPIRATOR.

Ventilation:PRVID GEN DILUT OR LOC EXHAUST VENT IN VOL TO KP BELOW TLV.

Protective Gloves:REQD F/REPEATED

Eye Protection:SAFETY EYEWEAR.

Other Protective Equipment:PRVNT PROLNG SKIN CONTACT OT CONTAMINATED CLOTHING.

Supplemental Safety and Health

UNUS FIRE & EXPOS HAZ:WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO VERY HOT SURFACES.

## Chemical Properties

HCC:F2

Boiling Pt:B.P. Text:175-246F

Vapor Density:HEAV

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:74

## Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES,HEAT, & HOT SURFACES.

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOC STATE & FEDERAL REGULATIONS.INCINTERATE IN APPRVD FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.